eurolite®

EUROLITE Set LED B-40 HCL Beam Effect + Soft Bag

Art. No.: 20000915 GTIN: 4026397701326



The article is no longer in our assortment.

Features:

EUROLITE LED B-40 HCL Beam Effect

LED beam effect with RGBAW+UV color mixing

- Precision lenses fill the room with countless rotating beams
- 5 powerful LEDs 12 W high-power 6in1 HCL RGBWA/UV
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Rotation speed stepless
- Multi beam effect; Strobe effect; UV effect
- 4 integrated show programs
- Direct color selection for 25 preset colors
- The device is cooled by low-noise cooling fan
- Control via DMX; Sound to light via Microphone; Master/slave function; stand-alone
- With Mounting bracket
- 4 digit 7-segment LED display
- Preprogrammed in Light J; LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
- Very quiet working noise
- Mains input and output for power linking up to 8 units Package contents
- 1 x light effect, 1 x user manual, 1 x power cord, 1 x omega bracket, 2 x screw, 2 x washer

EUROLITE SB-10 Soft Bag

Black soft bag with divider, 330 x 330 x 355 mm

- Practical transport bag offers enough space for several lighting effects and accessories
- With divider

Logistic

EAN / GTIN: 4026397701326 Weight: 7,00 kg Length: 0.00 m Width: 0.00 m Heigth: 0.00 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

- With Outside pocket
- High-quality workmanship with nylon , black, water repellent
- Interior with foam padding
- 2 Rugged carrying handles

Technical specifications:

Weight:

4,59 kg

EUROLITE LED B-40 HCL Beam Effect

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	50 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	IEC connector (F) mounting version
Lamp type:	LED lamp
LED:	5 x 12 W high-power 6in1 HCL RGBWA/UV
Flash rate:	0 - 20 Hz
DMX channels:	5; 11
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Low-noise cooling fan
Control:	DMX; Sound to light via Microphone; Master/slave function; stand-alone
Preprogrammed in:	Light J; LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 32 cm Depth: 32 cm Height: 38 cm
Weight:	4,15 kg
Noise classification:	Class 1 (very slight noise, suitable for noise- sensitive environments)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE SB-10 Soft Bag

Maximum load:

25 kg

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Carrying handle:	2 pc/pcs	
Material:	Nylon	
Color:	Black, water repellent	
Dimensions:	Width: 33 cm	
	Depth: 37 cm	
	Height: 33 cm	
Weight:	440 g	