

EUROLITE Set 4x AKKU Mini IP UP-4 QCL Spot + Case

Art. No.: 20000921

GTIN: 4026397695199



The article is no longer in our assortment.

Features:

EUROLITE AKKU Mini IP UP-4 QCL Spot

Mini battery uplight IP65 with RGBW LEDs and IR remote control

- Cordless, flexible and versatile
- Battery operation up to 9h depending on program used
- Integrated automatic charging of the battery
- 4 powerful LEDs 4 W 4in1 QCL RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable
- Strobe effect
- Direct color selection for 10 preset colors
- The device is cooled by passive convection cooling
- Control via sound to light via microphone; stand-alone; IR remote control
- Flicker-free
- With a beam angle of 19°
- With mounting bracket
- 4 digit 7-segment LED display
- Suitable for outdoor use IP65
- Silent operation

Package contents

- 1 x device, 1 x user manual, 1 x external mains adapter, 1 x remote control

Logistic

EAN / GTIN: 4026397695199

Weight: 11,00 kg

Length: 0.70 m

Width: 0.27 m

Height: 0.52 m

ROADINGER Flightcase 4x AKKU Mini IP UP-4 QCL Spot

- Interior with foam padding
cover with foam padding
- Aluminum profile frames 20mm with rounded edges

- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	9,25 kg
---------	---------

EUROLITE AKKU Mini IP UP-4 QCL Spot

Power supply:	100-240 V AC, 50/60 Hz 12,6V 1500 mA
Power consumption:	Max. 30 W
IP classification:	IP65
Protection class:	Protection class III
Power connection:	Battery/battery pack Mains input via coaxial power connector (M) mounting version
Battery pack type:	1 x 12,6 V, 3200 mAh, 40,32 Wh
Battery pack:	Battery operation up to 9h depending on program used Recharging time 2h
Lamp type:	LED lamp
LED type:	4 x 4 W 4in1 QCL RGBW (homogenous color mix)
Flash rate:	1 - 20 Hz
Cooling:	Passive convection cooling
Control:	Sound to light via microphone; stand-alone; IR remote control
Projection:	Flicker-free
Beam angle:	19°
Beam angle (1/2 peak):	19°
Beam angle (1/10 peak):	39°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Length: 10 cm Width: 11 cm Height: 12 cm
Weight:	1,25 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x button cell CR2025
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x AKKU Mini IP UP-4 QCL Spot

Maximum load:	25 kg
Aluminum profile frames:	20 mm
Use of brands:	Branded hardware
Color:	Dark brown, laminated
Device compartment:	11 cm x 10 cm x 12 cm
Inside dimensions:	54 cm x 20 cm x 13 cm
Accessory compartment:	54 cm x 8,5 cm x 13 cm
Material thickness:	6,5 mm
Dimensions:	Length: 58 cm Width: 24 cm Height: 17 cm
Weight:	4,25 kg