

# OMNITRONIC Set VHF-250 Wireless Mic Set + Transmitter + Armbelt 179MHzt. No.: 20000926 GTIN: 4026397707878









# The article is no longer in our assortment.

## Features:

#### **OMNITRONIC VHF-250 Wireless Mic Set 179**

Complete VHF diversity wireless microphone system

- Set includes receiver unit and one wireless microphone
- Switching diversity system with two folding antennas
- LED indicator for power, signal input and AF peak
- Output level control
- Squelch control to eliminate noise bursts
- XLR and 6.3 mm jack output
- Microphone with gain control
- License-free and approved in the EU (please check on a country-by-country basis)
- Operating range up to 50m
- License free in germany
- MicrophonePolar pattern: Cardioid
- Package contents
- 1 x receiver, 1 x external mains adapter, 1 x microphone, 1 x jack cable, 1 x user manual, 1 x declaration of conformity

#### OMNITRONIC TM-250 Transmitter VHF179.000

VHF bodypack transmitter set for TM-250

- Operation with fixed VHF frequency
- LED indicator for battery capacity
- 3.5 mm jack (1/8") screw connection to headset or lavalier mic
- Polar pattern: Cardioid

## Logistic

EAN / GTIN: 4026397707878 Weight: 2,00 kg Length: 0.46 m Width: 0.37 m Heigth: 0.27 m - Powered by a battery/battery pack

- License free in germany

# **Technical specifications:**

Weight:

1,64 kg

#### **OMNITRONIC VHF-250 Wireless Mic Set 179**

Туре:	Wireless set
Power connection:	Battery/battery pack
Number of channels:	1
Frequency range:	50 - 20,000 Hz
S/N ratio:	>90 dB
Range:	Range up to 50m
Frequency band:	VHF
Carrier frequency:	179 MHz
Diversity:	Antenna diversity
Frequency stability:	± 0,005 %
RF power output:	8,5 mW
Modulation:	FM
Frequency selection:	Fixed frequencies
Connections:	Output: Microphone via 1 x 3-pin XLR Output: Microphone via 1 x 6.3 mm plug (unbal.)
Material:	Plastic
Weight:	1,00 kg
Receiver	
Power supply:	230 V AC, 50 Hz 15 V DC 300 mA
Power consumption:	2,5 W
Power connection:	Mains input via Coaxial power connector (M) mounting version power supply cord with AC adapter (provided)
Microphone	
Power supply:	9 V DC
Capsule type:	Dynamic
Polar pattern:	Cardioid
Battery:	1 x 9.0 V E block 6F22 zinc carbon included
Switch:	On/off switch; Mute control
Dimensions:	Length: 26 cm Diameter: Ø 5 cm
Weight:	255 g

### OMNITRONIC TM-250 Transmitter VHF179.000

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Power connection:	Battery/battery pack
Capsule type:	Condenser
Polar pattern:	Cardioid
Battery:	1 x 9.0 V E block 6F22 zinc carbon included
THD:	<0,5 % at 1 kHz
Frequency band:	VHF
Carrier frequency:	179 MHz
Frequency stability:	± 0,03 %
RF power output:	8,5 mW
Modulation:	FM; F3F
Frequency selection:	Fixed frequencies
Connections:	Microphone via 1 x 3.5 mm jack (mono) mounting version screwable
Switch:	On/off switch
Material:	Plastic
Dimensions:	Width: 6,5 cm
	Depth: 3,2 cm
	Height: 10,7 cm
Weight:	170 g

## **OMNITRONIC** Armbelt for Pocket Receivers/Transmitters

Туре:	Bags/Belts
Color:	Black
Weight:	60 g