

EUROLITE Set 2x LED PLL-480 QCL Panel + Case

Art. No.: 20000932

GTIN: 4026397694598



List price: 2021.81 €

incl. 19% VAT.

Features:

EUROLITE LED PLL-480 QCL Panel

DMX-controlled surface light with 480 4in1 RGBW LEDs

- 480 powerful LEDs SMD 5050 4in1 QCL RGBW (homogenous color mix)
- Frost filter provides a soft, homogeneous light
- 4 barn doors to avoid blinding the audience and for protection during transport
- Silent operation
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; pulse-width modulation variable
- Strobe effect
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; master/slave function
- Flicker-free
- With a beam angle of 120°
- With mounting bracket
- LCD display
- Slim, rugged metal housing
- Stand or truss installation
- For application areas such as: Video and photography; stage; theater; advertisement/Shop window
- Preprogrammed in Light´J; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3
- Rugged carrying handle
- Mains input and output for power linking up to 8 units
- Application possibility: Suspended; on stand

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x plug (male)

Logistic

EAN / GTIN: 4026397694598

Weight: 41,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

ROADINGER Flightcase 2x LED PLL-480

- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Branded hardware

Technical specifications:

| | |
|---------|----------|
| Weight: | 37,50 kg |
|---------|----------|

EUROLITE LED PLL-480 QCL Panel

| | |
|--------------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 205 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) |
| Power output: | P-Con (gray), mounting version |
| Lamp type: | LED lamp |
| LED type: | 480 x SMD 5050 4in1 QCL RGBW (homogenous color mix) |
| Flash rate: | 1 - 19 Hz |
| DMX channels: | 6; 4 |
| DMX input: | 3-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |
| Cooling: | Passive convection cooling |
| Control: | DMX; stand-alone; master/slave function |
| Preprogrammed in: | Light´J; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3 |
| Projection: | Flicker-free |
| Beam angle: | 120° |
| Beam angle (1/2 peak): | 120° |
| Illuminance in Lux (lx): | Red (R) 1m: 438 lx, 3m: 61 lx, 6m: 18 lx Green (G) 1m: 633 lx, 3m: 88 lx, 6m: 25 lx Blue (B) 1m: 209 lx, 3m: 29 lx, 6m: 8 lx Cold white (CW) 1m: 2130 lx, 3m: 296 lx, 6m: 87 lx All 1m: 2696 lx, 3m: 380 lx, 6m: 112 lx |
| Lamp life: | 50000 h |
| Luminous flux: | 17103 lm |
| Housing color: | Black |
| Attachment system: | Mounting bracket |
| Display type: | LCD display |
| Carrying handle: | 1 pc/pcs |

| | |
|----------------------------------|---------------------------|
| Dimensions: | Width: 64 cm |
| | Depth: 13 cm |
| | Height: 33,5 cm |
| Weight: | 12,60 kg |
| Noise classification: | Class 0 (no noise at all) |
| Energy efficiency class (A - G): | F |
| EPREL-Nr: | 1243720 |

ROADINGER Flightcase 2x LED PLL-480

| | |
|------------------------|-------------------------|
| Maximum load: | 50 kg |
| Use of brands: | Branded hardware |
| Material: | Birch multiplex, 7 mm |
| Color: | Dark brown, laminated |
| Inside dimensions: | 64 cm x 38,5 cm x 29 cm |
| Device compartment: | 64 cm x 14 cm x 29 cm |
| Accessory compartment: | 64 cm x 10,5 cm x 29 cm |
| Dimensions: | Length: 70 cm |
| | Width: 47 cm |
| | Height: 39 cm |
| Weight: | 12,30 kg |