eurolite®

EUROLITE Set 2x LED Silent Par 6 QCL floor bk + Soft Bag

Art. No.: 20000964 GTIN: 4026397720914











List price: 332.01 €

incl. 19% VAT.

Features:

EUROLITE LED Silent Par 6 QCL floor bk

LED floor spot with RGB/WW color mixing

- 14350 lux at 1 m
- 6 powerful LEDs 8 W 4in1 QCL RGB/WW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) adjustable
- Strobe effect
- Direct color selection for 25 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; QuickDMX via USB (optional); master/slave function; sound to light via microphone
- Flicker-free
- With a beam angle of 16°
- With double bracket; with mounting bracket
- 4 digit 7-segment LED display
- Preprogrammed in Light'J; Light Captain; Colorchief
- For application areas such as: Clubs/dancing school; wedding/gala/events; Trade fair and shop fitting; stage; theater; restaurants, bars and hotels; mobile djs / entertainer
- Silent operation
- Application possibility: Standing; suspended; on stand
- Package contents
- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x XLR cable

EUROLITE SB-13 Soft Bag

Logistic

EAN / GTIN: 4026397720914 Weight: 6,00 kg Length: 0.00 m Width: 0.00 m Heigth: 0.00 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

- With 3 dividers
- With 4 compartments
- High-quality workmanship with nylon , black, water repellent
- Interior with foam padding
- 2 carrying straps
- Package contents
- 1 x bag

Technical specifications:

Weight:

4,56 kg

EUROLITE LED Silent Par 6 QCL floor bk

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	45 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Power output:	P-Con (gray), mounting version
LED type:	6 x 8 W 4in1 QCL RGB/WW (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	6; 11
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; QuickDMX via USB (optional); master/slave function; sound to light via microphone
Preprogrammed in:	Light'J; Light Captain; Colorchief
Projection:	Flicker-free
Beam angle:	16°
Beam angle (1/2 peak):	 16°
Beam angle (1/10 peak):	
Housing color:	Black
Attachment system:	Double bracket Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Length: 14,3 cm Width: 17,7 cm Height: 21,1 cm
Weight:	2,15 kg
Noise classification:	Class 0 (no noise at all)
Legal specifications	
Special product:	Not designed for household room illumination

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

EUROLITE SB-13 Soft Bag

Maximum load:	10 kg
Carrying strap:	2 pc/pcs
Material:	Nylon
Color:	Black, water repellent
Dimensions:	Length: 41 cm
	Depth: 16 cm
	Height: 19 cm
Weight:	0,26 kg