

OMNITRONIC Set FAS TWO + Dyn. Wireless Microphone + BP + Headset 660-690MHz

GTIN: 4026397723083



List price: 153.51 €

incl. 19% VAT.

Features:

OMNITRONIC FAS TWO 2-channel Wireless Receiver 660-690MHz

License-free miniature wireless microphone system, digital modulation, high ease of use

- 2 frequency banks with 20 adjustable frequencies each available
- Quick pairing at the touch of a button
- Receiver automatically adopts frequency setting
- Ultra-low latency
- Digital transmission provides for high resistance to interference and unique sound quality
- Small lightweight version
- Multiple receivers can be combined with 2 transmitters as desired
- Battery operation up to 5h
- Operating range up to 30m with line-of-sight
- Sample rate: 48 kHz
- Cordless, flexible and versatile
- UHF 660 - 690 MHz License-free and approved in large parts of Europe
- For application areas such as: Wedding/gala/events; mobile use; mobile djs / entertainer; restaurants, bars and hotels; small rental; product presentations and lectures

Package contents

- 1 x receiver, 1 x adapter, 1 x external mains adapter, 1 x USB cable, 1 x user manual, 1 x declaration of conformity

Logistic

EAN / GTIN: 4026397723083

Weight: 1,10 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

OMNITRONIC FAS Dynamic Wireless Microphone 660-690MHz

Dynamic hand-held microphone for FAS-TWO receiver

- Digital transmission provides for high resistance to interference and unique sound quality
- Quick pairing at the touch of a button

- 2 frequency banks with 20 adjustable frequencies each available
- Rugged, ergonomic aluminum housing
- Polar pattern: Cardioid
- Operating range up to 30m with line-of-sight
- UHF 660 - 690 MHz License-free and approved in large parts of Europe
- Charge status indicator

Package contents

- 1 x transmitter, 1 x user manual, 1 x declaration of conformity

OMNITRONIC FAS Bodypack 660-690MHz

Minature bodypack transmitter for FAS-TWO receiver

- Digital transmission provides for high resistance to interference and unique sound quality
- Ultra-low latency
- Quick pairing at the touch of a button
- Receiver automatically adopts frequency setting
- 2 frequency banks with 20 adjustable frequencies each available
- Small lightweight version
- Battery operation up to 5h
- Operating range up to 30m with line-of-sight
- Wide range of microphones available for numerous applications
- Cordless, flexible and versatile
- UHF 660 - 690 MHz License-free and approved in large parts of Europe

Package contents

- 1 x transmitter, 1 x user manual, 1 x declaration of conformity

OMNITRONIC FAS Headset for Bodypack

Accessory microphone for FAS bodypack

- Polar pattern: Omnidirectional
- For application areas such as: Clubs/dancing school; sports centres/gyms

Package contents

- 1 x microphone, 1 x user manual

Technical specifications:

Weight:	0,85 kg
---------	---------

OMNITRONIC FAS TWO 2-channel Wireless Receiver 660-690MHz

Type:	Receiver
Power supply:	5V DC 1000 mA
Power connection:	Mains input via USB C (W) mounting version power supply cord with AC adapter included Battery/battery pack built-in
Battery pack type:	1 x lithium ion 3,7 V, 800 mAh, 3,96 Wh
Battery pack:	Battery operation up to 5h
Number of channels:	2
Frequency range:	60 - 15000 Hz
S/N ratio:	>92 dB
THD:	<0,8 % at 1 kHz
Range:	Range up to 30m with line-of-sight
Frequency band:	UHF 660 - 690 MHz

Modulation:	Pi/4 DQPSK
Frequency selection:	40 In 2 groups Frequencies automatically scannable Switchable frequencies
Sample rate:	48 kHz
Status LED:	Power, chanal source
Connections:	Output: mic/line via 1 x 3.5 mm jack (mono)
Max. level:	Output: mic/line -1,90 dBu, unbal.
Material:	Metal
Color:	Black
Weight:	0,14 kg
Receiver	
Dimensions:	Length: 17 cm Width: 3,6 cm Height: 2,2 cm
Weight:	0,05 kg

OMNITRONIC FAS Dynamic Wireless Microphone 660-690MHz

Power supply:	3V DC
Power connection:	Battery/battery pack
Capsule type:	Dynamic
Polar pattern:	Cardioid
Battery:	2 x Mignon (AA) (not included)
Range:	Range up to 30m with line-of-sight
Frequency band:	UHF 660 - 690 MHz
RF power output:	10 mW
Modulation:	Pi/4 DQPSK
Frequency selection:	40 switchable frequencies In 2 groups
Display:	Frequency , charge status indicator
Switch:	On/off switch
Material:	Metal
Color:	Black
Dimensions:	Length: 25,5 cm Diameter: Ø 5,3 cm
Weight:	0,29 kg

OMNITRONIC FAS Bodypack 660-690MHz

Type:	Pocket transmitter
Power supply:	5V DC 1000 mA
Power connection:	Mains input via USB C (W) mounting version Battery/battery pack built-in
Battery pack type:	1 x lithium ion 3,7 V, 600 mAh, 2,2 Wh

Battery pack:	Battery operation up to 5h
Number of channels:	1
Range:	Range up to 30m with line-of-sight
Frequency band:	UHF 660 - 690 MHz
RF power output:	10 mW
Modulation:	Pi/4 DQPSK
Frequency selection:	40 In 2 groups Frequencies automatically scannable Switchable frequencies
Status LED:	Power
Connections:	Input: mic/line via 1 x 3.5 mm jack (stereo) mounting version
Max. level:	Input: mono -1,5 dBu, unbal.
Material:	Plastic
Color:	Black
Dimensions:	Length: 21 cm Width: 3,05 cm Height: 2,9 cm
Weight:	0,034 kg

OMNITRONIC FAS Headset for Bodypack

Type:	Headset microphone
Power supply:	2-10V DC
Cable length:	1,2 m
Capsule type:	Condenser Size: Ø 3 mm x 1,5 mm
Polar pattern:	Omnidirectional
Frequency range:	20 - 18000 Hz
S/N ratio:	>63 dB
Sensitivity:	-47 dB
Impedance:	680 Ohm
Connections:	3.5 mm jack (mono)
Material:	Metal
Color:	Skin-colored
Weight:	0,02 kg