

**List price: 136.85 €**

incl. 19% VAT.

**Features:****OMNITRONIC FAS TWO 2-channel Wireless Receiver 660-690MHz**

License-free miniature wireless microphone system, digital modulation, high ease of use

- 2 frequency banks with 20 adjustable frequencies each available
- Quick pairing at the touch of a button
- Receiver automatically adopts frequency setting
- Ultra-low latency
- Digital transmission provides for high resistance to interference and unique sound quality
- Small lightweight version
- Multiple receivers can be combined with 2 transmitters as desired
- Battery operation up to 5h
- Operating range up to 30m with line-of-sight
- Sample rate: 48 kHz
- Cordless, flexible and versatile
- UHF 660 - 690 MHz License-free and approved in large parts of Europe
- For application areas such as: Wedding/gala/events; mobile use; mobile djs / entertainer; restaurants, bars and hotels; small rental; product presentations and lectures

**Package contents**

- 1 x receiver, 1 x adapter, 1 x external mains adapter, 1 x USB cable, 1 x user manual, 1 x declaration of conformity

**Logistic**

EAN / GTIN: 4026397723106

Weight: 1,30 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

**OMNITRONIC FAS Dynamic Wireless Microphone 660-690MHz**

Dynamic hand-held microphone for FAS-TWO receiver

- Digital transmission provides for high resistance to interference and unique sound quality
- Quick pairing at the touch of a button

- 2 frequency banks with 20 adjustable frequencies each available
  - Rugged, ergonomic aluminum housing
  - Polar pattern: Cardioid
  - Operating range up to 30m with line-of-sight
  - UHF 660 - 690 MHz License-free and approved in large parts of Europe
  - Charge status indicator
- Package contents**
- 1 x transmitter, 1 x user manual, 1 x declaration of conformity

Technical specifications:

|         |         |
|---------|---------|
| Weight: | 0,99 kg |
|---------|---------|

OMNITRONIC FAS TWO 2-channel Wireless Receiver 660-690MHz

|                      |   |
|----------------------|---|
| Type:                | Receiver  |
| Power supply:        | 5V DC 1000 mA   |
| Power connection:    | Mains input via USB C (W) mounting version<br>power supply cord with AC adapter included<br>Battery/battery pack built-in |
| Battery pack type:   | 1 x lithium ion 3,7 V, 800 mAh, 3,96 Wh   |
| Battery pack:        | Battery operation up to 5h  |
| Number of channels:  | 2   |
| Frequency range:     | 60 - 15000 Hz   |
| S/N ratio:           | >92 dB  |
| THD:                 | <0,8 % at 1 kHz   |
| Range:               | Range up to 30m with line-of-sight  |
| Frequency band:      | UHF 660 - 690 MHz   |
| Modulation:          | Pi/4 DQPSK  |
| Frequency selection: | 40<br>In 2 groups<br>Frequencies automatically scannable<br>Switchable frequencies  |
| Sample rate:         | 48 kHz  |
| Status LED:          | Power, chanal source  |
| Connections:         | Output: mic/line via 1 x 3.5 mm jack (mono)   |
| Max. level:          | Output: mic/line -1,90 dBu, unbal.  |
| Material:            | Metal   |
| Color:               | Black   |
| Weight:              | 0,14 kg   |
| Receiver             |   |
| Dimensions:          | Length: 17 cm<br>Width: 3,6 cm<br>Height: 2,2 cm  |
| Weight:              | 0,05 kg   |

**OMNITRONIC FAS Dynamic Wireless Microphone 660-690MHz**

|                      |  |
|----------------------|--|
| Power supply:        | 3V DC                                    |
| Power connection:    | Battery/battery pack                     |
| Capsule type:        | Dynamic                                  |
| Polar pattern:       | Cardioid                                 |
| Battery:             | 2 x Mignon (AA) (not included)           |
| Range:               | Range up to 30m with line-of-sight       |
| Frequency band:      | UHF 660 - 690 MHz                        |
| RF power output:     | 10 mW                                    |
| Modulation:          | Pi/4 DQPSK                               |
| Frequency selection: | 40 switchable frequencies<br>In 2 groups |
| Display:             | Frequency , charge status indicator      |
| Switch:              | On/off switch                            |
| Material:            | Metal                                    |
| Color:               | Black                                    |
| Dimensions:          | Length: 25,5 cm<br>Diameter: Ø 5,3 cm    |
| Weight:              | 0,29 kg                                  |