



Features:**OMNITRONIC FAS TWO 2-channel Wireless Receiver 660-690MHz**

License-free miniature wireless microphone system, digital modulation, high ease of use

- 2 frequency banks with 20 adjustable frequencies each available
- Quick pairing at the touch of a button
- Receiver automatically adopts frequency setting
- Ultra-low latency
- Digital transmission provides for high resistance to interference and unique sound quality
- Small lightweight version
- Multiple receivers can be combined with 2 transmitters as desired
- Sample rate: 48 kHz
- Operating range up to 30m with line-of-sight
- UHF 660 - 690 MHz License-free and approved in large parts of Europe
- For application areas such as: Wedding/gala/events; mobile use; mobile djs / entertainer; restaurants, bars and hotels; small rental; product presentations and lectures

battery pack

- Cordless, flexible and versatile
- Battery operation up to 5h

OMNITRONIC FAS Dynamic Wireless Microphone 660-690MHz

Dynamic hand-held microphone for FAS-TWO receiver

- Digital transmission provides for high resistance to interference and unique sound quality
- Quick pairing at the touch of a button
- 2 frequency banks with 20 adjustable frequencies each available
- Rugged, ergonomic aluminum housing

Logistic

EAN / GTIN: 4026397723106

Weight: 1,30 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

- Polar pattern: Cardioid
- Operating range up to 30m with line-of-sight
- UHF 660 - 690 MHz License-free and approved in large parts of Europe
- Charge status indicator

Technical specifications:

Weight: 0.76 kg

OMNITRONIC FAS TWO 2-channel Wireless Receiver 660-690MHz

Type:	Receiver
Power supply:	100-240 V AC, 50/60 Hz 5V DC 1000 mA
Power connection:	Mains input via USB C (W) mounting version power supply cord with AC adapter included
Number of channels:	2
Frequency range:	60 - 15000 Hz
S/N ratio:	>92 dB
THD:	<0.8 % at 1 kHz
Range:	Range up to 30m with line-of-sight
Frequency band:	UHF 660 - 690 MHz
Modulation:	Pi/4 DQPSK
Frequency selection:	40 In 2 groups Frequencies automatically scannable Switchable frequencies
Sample rate:	48 kHz
Status LED:	Power, channel source
Connections:	Output: mic/line via 1 x 3.5 mm jack (mono)
Channels:	Microphone channel: 2 x mono
Max. level:	Output: mic/line -1.90 dBu, unbal.
Color:	Black
Weight:	0.14 kg
Material:	Metal
Dimensions:	Length: 17 cm Width: 3.6 cm Height: 2.2 cm
Weight:	0.05 kg
Power connection:	Battery/battery pack built-in
Battery pack type:	1 x lithium ion 3.7 V, 800 mAh, 3.96 Wh
Battery pack:	Battery operation up to 5h

OMNITRONIC FAS Dynamic Wireless Microphone 660-690MHz

Power supply:	3V DC
Power connection:	Battery/battery pack
Capsule type:	Dynamic
Polar pattern:	Cardioid
Battery:	2 x Mignon (AA) (not included)
Range:	Range up to 30m with line-of-sight
Frequency band:	UHF 660 - 690 MHz
RF power output:	10 mW
Modulation:	Pi/4 DQPSK
Frequency selection:	40 switchable frequencies In 2 groups
Display:	Frequency , channel , charge status indicator
Switch:	On/off switch
Material:	Metal
Color:	Black
Dimensions:	Length: 25.5 cm Diameter: Ø 5.3 cm
Weight:	0.31 kg

Scope of delivery:

1 x OMNITRONIC FAS TWO 2-channel Wireless Receiver 660-690MHz

1 x receiver
 1 x adapter
 1 x external mains adapter
 1 x USB cable
 1 x user manual
 1 x declaration of conformity

2 x OMNITRONIC FAS Dynamic Wireless Microphone 660-690MHz

1 x transmitter
 1 x user manual
 1 x declaration of conformity