

OMNITRONIC Set UHF-E2 Wireless Mic System + 2x BP + 2x Lavalier Microphone ชื่อสิริโว29.

GTIN: 4026397724431



List price: 201.11 €

incl. 19% VAT.

Features:

OMNITRONIC UHF-E2 Wireless Mic System 527.5/529.7MHz

License-free 2-channel wireless microphone system

- 2-channel receiver and 2 hand-held microphones with UHF PLL technology
- Easy handling
- 2 separate channels with volume controls and LEDs for carrier signal and audio signal
- Balanced XLR output per channel
- 6.3 mm jack for mixed signal output
- Microphones with color indication
- Operating range up to 60m with line-of-sight
- UHF 518 548 MHz License-free and approved in large parts of Europe
- For application areas such as: Clubs/dancing school; Wedding/gala/events; mobile use; mobile djs / entertainer; small rental
- Up to 12 transmitters can be operated in parallel without interference

Receiver

- Desktop console housing
- (19") 48.3 cm rack installation possible 1 U

Microphone

- Polar pattern: Cardioid

Package contents

- 1 x receiver, 2 x antenna, 1 x external mains adapter, 2 x microphone, 1 x jack cable, 3 x mounting bracket, 3 x screw, 4 x foot, 1 x user manual, 1 x declaration of conformity

OMNITRONIC UHF-E Series Bodypack 527.5MHz + Lavalier Microphone

Bodypack transmitter with lavalier microphone for UHF-E receivers

Logistic

EAN / GTIN: 4026397724431

Weight: 3,00 kg Length: 0.00 m Width: 0.00 m Heigth: 0.00 m

- Sensitivity adjustable
- Polar pattern: Cardioid
- Operating range up to 60m with line-of-sight
- UHF 518 548 MHz License-free and approved in large parts of Europe

Package contents

- 1 x transmitter, 1 x microphone, 2 x battery, 1 x user manual, 1 x declaration of conformity

OMNITRONIC UHF-E Series Bodypack 529.7MHz + Lavalier Microphone

Bodypack transmitter with lavalier microphone for UHF-E receivers

- Sensitivity adjustable
- Polar pattern: Cardioid
- Operating range up to 60m with line-of-sight
- UHF 518 548 MHz License-free and approved in large parts of Europe

Package contents

- 1 x transmitter, 1 x microphone, 2 x battery, 1 x user manual, 1 x declaration of conformity

Technical specifications:

Weight:	2,63 kg	
---------	---------	--

OMNITRONIC UHF-E2 Wireless Mic System 527.5/529.7MHz

Type:	Wireless set	
Range:	Range up to 60m with line-of-sight	
Frequency band:	UHF 518 - 548 MHz	
Carrier frequency:	527,5; 529,7	
Parallel mode:	Max. 12 transmitter	
Modulation:	FM	
Frequency selection:	Fixed frequencies	
Color code:	CH A= blue, CH B= grey,	
Weight:	1,82 kg	
Receiver		
Power supply:	100-240 V AC, 50/60 Hz	
	13,5 V DC 150 mA	
Power consumption:	6 W	
Power connection:	Mains input via Coaxial power connector (M) mounting version power supply cord with AC adapter (provided)	
Number of channels:	2	
Frequency range:	20 - 20000 Hz	
S/N ratio:	>96 dB	
THD:	<0,1 % at 1 kHz	
Housing color:	Black	
Control elements:	Power switch, level control	
Connections:	Output: line via 1 x 6.3 mm plug (unbal.)	
	Output: Microphone via 2 x 3-pin XLR	
Material:	Metal	

Housing design:	Desktop console housing	
	(19") 48.3 cm rack installation possible 1 U	
Weight:	1 kg	
Microphone		
Type:	Hand-held transmitter	
Power supply:	3 V DC	
Power connection:	Battery/battery pack	
Capsule type:	Dynamic	
Polar pattern:	Cardioid	
Battery:	2 x Mignon (AA) (not included)	
Frequency range:	50 - 20000 Hz	
RF power output:	10 mW	
Housing color:	Black	
Switch:	Mute control	
Material:	Plastic	
Dimensions:	Length: 25 cm	
	Diameter: Ø 5,2 cm	
Weight:	205 g	

OMNITRONIC UHF-E Series Bodypack 527.5MHz + Lavalier Microphone

3 V DC	
Battery/battery pack	
Condenser	
Cardioid	
2 x Mignon (AA) (not included)	
<0,1 % at 1 kHz	
Range up to 60m with line-of-sight	
UHF 518 - 548 MHz	
527,5 MHz	
10 mW	
FM	
Fixed frequencies	
Mini XLR (M) 3-pin mounting version	
Charge status indicator	
On/off switch	
Plastic	
Black	
Width: 6,8 cm	
Depth: 2,3 cm	
Height: 10 cm	
140 g	

OMNITRONIC UHF-E Series Bodypack 529.7MHz + Lavalier Microphone

Type:	Pocket transmitter	
Power supply:	3 V DC	
Power connection:	Battery/battery pack	
Capsule type:	Condenser	
Polar pattern:	Cardioid	
Battery:	2 x Mignon (AA) (not included)	
THD:	<0,1 % at 1 kHz	
Range:	Range up to 60m with line-of-sight	
Frequency band:	UHF 518 - 548 MHz	
Carrier frequency:	529,7 MHz	
RF power output:	10 mW	
Modulation:	FM	
Frequency selection:	Fixed frequencies	
Connector type:	Mini XLR (M) 3-pin mounting version	
Status LED:	Charge status indicator	
Switch:	On/off switch	
Material:	Plastic	
Color:	Black	
Dimensions:	Width: 6,8 cm	
	Depth: 2,3 cm	
	Height: 10 cm	
Weight:	140 g	