

EUROLITE Set LED KLS Scan Pro Next FX Compact Light Set + BPS-3 Loudspeaker Stand b

GTIN: 4026397280050



List price: 1426.81 €

incl. 19% VAT.

Features:

EUROLITE LED KLS Scan Pro Next FX Compact Light Set

Compact bar with derby, spots, scanners, UV effect, QuickDMX port and bag

- Heart gobo for romantic occasions
 - Positioning within TILT
 - Gobo wheel with static gobos, 7 gobos and open
 - Color wheel; gobo wheel with static gobos
 - Color wheel with 7 dichroic filters plus open
 - 20 integrated show programs
 - Program selection; Dimmer electronic; color blend stepless
 - Strobe effect; multi beam effect; UV effect
 - Control via stand-alone; sound to light via microphone; master/slave function; IR remote control; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); wireless footswitch (optional); quick select potentiometer for brightness
 - Flicker-free
 - OLED display
 - For application areas such as: Wedding/gala/events; mobile use; stage; mobile djs / entertainer
 - Mains input and output for power linking up to 8 units
 - Preprogrammed in Light Captain; EASY SHOW 2; EASY SHOW 3
 - The article is delivered with practical transport bag
 - The article is delivered pre-assembled
 - Application possibility: Suspended; on stand
- spotlight**
- 5 powerful LEDs 7 W high-power 4in1 QCL RGB/WW (homogenous color mix)
4 spots controlled separately
 - With a beam angle of 15°

Logistic

EAN / GTIN: 4026397280050

Weight: 35,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

Bulky product

light effect

- 2 powerful LEDs 3 W R/G/B

moving light

- 1 powerful LED 37,5 W cold white (CW)

bar

- 4 powerful LEDs 1 W high-power ultra violet (UV)
 LEDs controlled separately

Package contents

- 1 x device, 1 x user manual, 1 x power cord, 1 x declaration of conformity, 2 x mounting bracket, 1 x remote control, 1 x battery, 1 x bag, 2 x knurled screw, 2 x washer

EUROLITE STV-3529 Adapter long

Massive adapter for 35 mm tube, 28 mm TV spigot, maximum load WLL 100 kg

- For stands with telescopic tube 35 mm
- Connection element for cross beam with 28 mm TV spigot
- With M6 and M8 fixation screw
- Heavy version for highest stability
- TV spigot

Package contents

- 1 x device, 1 x user manual, 2 x knurled screw

Technical specifications:

Weight:	27,80 kg
---------	----------

EUROLITE LED KLS Scan Pro Next FX Compact Light Set

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	265 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Cable construction:	H05VV-F
Power output:	1 x P-Con (gray), mounting version
Fuse:	5 x 20 mm, T 5 A fuse replaceable
Equipment:	Color wheel; gobo wheel with static gobos
Color generation:	Color wheel with 7 dichroic filters plus open
Gobos:	Gobo wheel with static gobos, 7 gobos and open
DMX channels:	3; 7; 13; 14; 15; 18; 19; 30; 32; 39
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; sound to light via microphone; master/slave function; IR remote control; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); wireless footswitch (optional); quick select potentiometer for brightness
Preprogrammed in:	Light Captain; EASY SHOW 2; EASY SHOW 3

Projection:	Flicker-free
Housing color:	Black
Attachment system:	TV spigot Ø 28mm 2x mounting bracket
Display type:	OLED display
Dimensions:	Length: 112 cm Depth: 10 cm Height: 42 cm
Weight:	13,30 kg
Noise classification:	Class 3 (clearly perceptible sounds)
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Bar	
LED type:	4 x 1 W high-power ultra violet (UV)
Illuminance in Lux (lx):	Ultra violet (UV) 1m: 30 lx, 3m: 4 lx, 6m: 1 lx
Light effect	
LED type:	2 x 3 W R/G/B
Spotlight	
LED type:	5 x 7 W high-power 4in1 QCL RGB/WW (homogenous color mix)
Beam angle:	15°
Beam angle (1/2 peak):	15°
Beam angle (1/10 peak):	30°
Illuminance in Lux (lx):	Spot red (R) 1m: 2300 lx, 3m: 235 lx, 6m: 58 lx Spot green (G) 1m: 4187 lx, 3m: 422 lx, 6m: 107 lx Spot blue (B) 1m: 760 lx, 3m: 78 lx, 6m: 20 lx Spot warm white (WW) 1m: 3290 lx, 3m: 325 lx, 6m: 85 lx Spot all 1m: 10283 lx, 3m: 1010 lx, 6m: 259 lx
Moving light	
LED type:	1 x 37,5 W cold white (CW)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

OMNITRONIC BPS-3 Loudspeaker Stand black

Weight:	13,00 kg
---------	----------

EUROLITE STV-3529 Adapter long

Maximum load BGV C1 (8-fold):	50 kg
Maximum load WLL (4-fold):	100 kg
Attachment system:	TV spigot Ø 28mm Ø 35mm

Type (general stands):	Accessory
Material:	Steel, 6 mm, powder-coated
Dimensions:	Width: 8,50 cm Depth: 5 cm Height: 19,50 cm
Weight:	1,50 kg