

EUROLITE Set 8x LED IP PAR 7x10W RGBL Spot + Case

Art. No.: 20000980

GTIN: 4026397726015







List price: 3211.81 €

incl. 19% VAT.

Features:

EUROLITE LED IP PAR 7x10W RGBL spot

IP65 spotlight with RGBL LEDs, frost filters and IR remote control

- Two additional frost filters provide a soft, homogeneous light
- 7 powerful LEDs 10 W high-power 4in1 QCL RGBL (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) with adjustable response; white balance
- Strobe effect
- 36 integrated show programs
- Direct color selection for 15 preset colors
- The device is cooled by passive convection cooling
- Control via IR remote control; stand-alone; DMX; master/slave function; sound to light via microphone
- Preprogrammed in Light Captain; Colorchief
- Flicker-free
- With a beam angle of 10°
- With double bracket
- OLED display
- Mains input and output for power linking up to 8 units
- Suitable for outdoor use
- With pressure compensation membrane
- With a KENSINGTON LOCK theft protection
- For application areas such as: Installation; stage; rental; architecture
- Silent operation
- Application possibility: Standing; suspended; on stand
- 3 buttons on the remote control for saving your own settings

Package contents

Logistic

EAN / GTIN: 4026397726015

Weight: 65,00 kg Length: 0.00 m Width: 0.00 m Heigth: 0.00 m Bulky product 1 x device, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery, 2 x frost filter, 2 x screw, 1 x mounting bracket

ROADINGER Flightcase 8x LED IP PAR 7x10W RGBL

Trunk case with castors

- High-quality workmanship with plywood multi-layer glued 7 mm, black, laminated
- Interior with foam padding
cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 castors
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 57,30 kg

EUROLITE LED IP PAR 7x10W RGBL spot

EUROLITE LED IF PAR /XIUW ROOL	spot
Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	75 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug
Power output:	IP T-Con (F) mounting version
Lamp type:	LED lamp
LED type:	7 x 10 W high-power 4in1 QCL RGBL (homogenous color mix)
Flash rate:	1 - 23 Hz
DMX channels:	3; 4; 6; 8; 11
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	IR remote control; stand-alone; DMX; master/slave function; sound to light via microphone
Preprogrammed in:	Light Captain; Colorchief
Projection:	Flicker-free
Beam angle:	10°
Beam angle (1/2 peak):	10°
	Frost filter 15°
	Frost filter 19°
Beam angle (1/10 peak):	20°
Housing color:	Black
Attachment system:	Double bracket

Display type:	OLED display
Theft protection:	KENSINGTON LOCK
Dimensions:	Length: 23,4 cm Width: 28 cm Height: 17 cm
Weight:	4,25 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 8x LED IP PAR 7x10W RGBL

Aluminum profile frames:	30 mm
Case handle:	4 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors
Material:	Plywood multi-layer glued, 7 mm
Color:	Black, laminated
Device compartment:	18 cm x 25 cm x 26 cm
Accessory compartment:	6,5 cm x 52 cm x 26 cm
Inside dimensions:	86,5 cm x 51,5 cm x 26 cm
Dimensions:	Width: 92 cm
	Depth: 57 cm
	Height: 47,5 cm
Weight:	23,30 kg