



List price: 1069.81 €

incl. 19% VAT.

Features:

EUROLITE LED Silent Par 6 QCL floor bk

LED floor spot with RGB/WW color mixing

- 14350 lux at 1 m
- 6 powerful LEDs 8 W 4in1 QCL RGB/WW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) adjustable
- Strobe effect
- Direct color selection for 25 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; QuickDMX via USB (optional); Master/slave function; Sound to light via Microphone
- Flicker-free
- With a beam angle of 16°
- With double bracket; with panning and tilting mounting bracket for ceiling or wall installation in most varying angles
- 4 digit 7-segment LED display
- Preprogrammed in Light´J; Light Captain
- For application areas such as: Clubs/dancing school; Wedding/gala/events; Trade fair and shop fitting; Stage; theater; restaurants, bars and hotels; mobile djs / entertainer
- Silent operation
- Application possibility: Standing; suspended; on stand

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x xLR cable

Logistic

EAN / GTIN: 4026397728224

Weight: 20,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

ROADINGER Flightcase 4x SILENT PAR 6 QCL FLOOR

PRO flightcase for 4 x SILENT PAR 6 QCL FLOOR

- High-quality workmanship with birch multiplex 7 mm, black
- Interior with felt cover
cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 3 hinged, chromium plated case handles
- Branded hardware
- 4 rubber feet
- Made in Europe

Technical specifications:

Weight: 17,20 kg

EUROLITE LED Silent Par 6 QCL floor bk

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	45 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Power output:	P-Con (gray), mounting version
LED:	6 x 8 W 4in1 QCL RGB/WW (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	6; 11
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; QuickDMX via USB (optional); Master/slave function; Sound to light via Microphone
Preprogrammed in:	Light J; Light Captain
Projection:	Flicker-free
Beam angle:	16°
Beam angle (1/2 peak):	16°
Beam angle (1/10 peak):	29°
Housing color:	Black
Attachment system:	Double bracket Panning and tilting mounting bracket for ceiling or wall installation in most varying angles
Display type:	4 digit 7-segment LED display
Dimensions:	Length: 14,3 cm Width: 17,7 cm Height: 21,1 cm

Weight:	2,15 kg
Noise classification:	Class 0 (no noise at all)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x SILENT PAR 6 QCL FLOOR

Aluminum profile frames:	30 mm
Case handle:	3 pc/pcs
Transport aid:	4 x rubber feet
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Black
Device compartment:	15 cm x 14 cm x 20 cm
Accessory compartment:	11 cm x 30 cm x 21 cm
Inside dimensions:	44 cm x 30 cm x 21 cm
Dimensions:	Width: 48,5 cm Depth: 35 cm Height: 30 cm
Weight:	8,60 kg