



List price: 474.81 €

incl. 19% VAT.

Features:

EUROLITE LED PIX-16 QCL Bar

LED light effect bar with 16 x 4 W RGBW LED (4in1), incl. IR remote control

- 16 powerful LEDs 4 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
- Strobe effect
- 21 integrated show programs
- Direct color selection for 15 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; Master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); Sound to light via Microphone; IR remote control
- Preprogrammed in Light´J; Light Captain
- Flicker-free
- With a beam angle of 15°
- With Mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; Party room; Installation; restaurants, bars and hotels
- Silent operation
- Application possibility: Suspended; Wall mounting

Package contents

- 1 x bar, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery, 2 x mounting bracket, 2 x screw, 2 x washer

Logistic

EAN / GTIN: 4026397728415

Weight: 7,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

EUROLITE SB-12 Soft Bag

Practical black soft bag for LED bars (1 m length), adjustable divider

- Ideal for 1 or 2 LED bars with 1 meter length
- Made of easy-care nylon
- With divider
- With 2 Device compartments
- High-quality workmanship with textile , black
- Interior with foam padding
- 2 carrying straps
- 1 shoulder strap

Technical specifications:

Weight: 5,35 kg

EUROLITE LED PIX-16 QCL Bar

| | |
|-------------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 70 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug |
| Power output: | P-Con (gray), mounting version |
| Fuse: | F 1 A Fuse replaceable |
| Lamp type: | LED lamp |
| LED: | 16 x 4 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix) |
| DMX channels: | 3; 4; 11; 21-1; 21-2; 64 |
| DMX input: | 3-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |
| Cooling: | Passive convection cooling |
| Control: | Stand-alone; Master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); Sound to light via Microphone; IR remote control |
| Preprogrammed in: | Light J; Light Captain |
| Projection: | Flicker-free |
| Beam angle: | 15° |
| Beam angle (1/2 peak): | 15° |
| Beam angle (1/10 peak): | 30° |
| Housing color: | Black |
| Attachment system: | 2x Mounting bracket |
| Display type: | 4 digit 7-segment LED display |
| Dimensions: | Length: 1,08 m |

| | |
|-----------------------|---|
| | Width: 6,5 cm |
| | Height: 8,5 cm |
| Weight: | 2,39 kg |
| Noise classification: | Class 0 (no noise at all) |
| Remote control | |
| Battery: | 1 x Button cell 3.0 V CR2025 lithium manganese built-in |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

EUROLITE SB-12 Soft Bag

| | |
|-----------------|--|
| Maximum load: | 20 kg |
| Carrying strap: | 2 pc/pcs |
| Transport aid: | 1 x shoulder strap |
| Material: | Textile |
| Color: | Black |
| Dimensions: | Width: 1,07 m Depth: 17 cm Height: 18 cm |
| Weight: | 570 g |