



Features:

EUROLITE LED PMB-4 COB QCL 30W Bar

LED light effect bar with RGBW color mixing, incl. IR remote control

- 4 LEDs 30 W COB (chip-on-board) 4in1 RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- Integrated show programs
- Direct color selection for 27 preset colors
- The device is cooled by low-noise cooling fan
- Control via stand-alone; IR remote control; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Fixtures available for Light Captain; EASY SHOW 2; EASY SHOW 1; EASY SHOW 3; Light J; Colorchief
- Flicker-free
- With a beam angle of 45°
- With mounting bracket
- LCD display
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; clubs/dancing school; wedding/gala/events; Trade fair and shop fitting; restaurants, bars and hotels; theater; rental; video and photography; advertisement/Shop window
- Very quiet working noise
- Application possibility: Standing; suspended; on stand

Logistic

EAN / GTIN: 4026397527940

Weight: 43,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

Bulky product

ROADINGER Flightcase 4x LED PMB-4 COB QCL with wheels

Trunk case with castors, PRO version

- High-quality workmanship with birch multiplex 9 mm, black, laminated
- Interior with foam padding
cover with foam padding
- Aluminum profile frames 25mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 x castors with 2 locking brakes
- PENN Hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 41.65 kg

EUROLITE LED PMB-4 COB QCL 30W Bar

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	110 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Fuse:	T 2 A fuse replaceable
Lamp type:	LED lamp
LED type:	4 x 30 W COB (chip-on-board) 4in1 RGBW (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	3; 4; 5; 6; 8; 16; 20
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	2 x low-noise cooling fan
Control:	Stand-alone; IR remote control; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W- DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	Light Captain; EASY SHOW 2; EASY SHOW 1; EASY SHOW 3; Light J; Colorchief
Projection:	Flicker-free
Beam angle (1/2 peak):	45°
Beam angle (1/10 peak):	74°
Housing color:	Black
Attachment system:	Mounting bracket

Display type:	LCD display
Material:	Aluminum casting; metal
Dimensions:	Length: 49.0 cm Depth: 16.3 cm Height: 20.6 cm
Weight:	5.75 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Photobiological safety:	Risk Group 0
Diameter mounting holes:	3 x Ø11mm; 1 x Ø10mm; 2 x Ø8mm; 2 x Ø6mm
Material:	Metal, 3 mm
Cable construction:	3 x 1.0 mm ² H05RN-F
Cable length:	Approx. 1.2 m
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x LED PMB-4 COB QCL with wheels

Maximum load:	100 kg
Aluminum profile frames:	25 mm
Case handle:	4 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes
Use of brands:	PENN Hardware
Material:	Birch multiplex, 9 mm
Color:	Black, laminated
Device compartment:	12 cm x 50 cm x 26 cm
Accessory compartment:	9 cm x 52 cm x 28 cm
Dimensions:	Width: 89 cm Depth: 56 cm Height: 47 cm
Weight:	18.65 kg

Scope of delivery:

- 1 x light effect
- 1 x power cord
- 1 x remote control
- 1 x battery
- 1 x user manual