

EUROLITE Set GoFlow 100 + Soft Bag

Art. No.: 20000998 GTIN: 4026397684070





List price: 415.31 €

incl. 19% VAT.

EAN / GTIN: 4026397684070

Features: Logistic

EUROLITE GoFlow 100

Extremely bright gobo flower with separate color/gobo wheel and 2 rotation functions

- 1 powerful LED 100 W COB (chip-on-board) cold white (CW)
- Gobo wheel with rotating gobos; color wheel
- Dimmer electronic
- Flower effect; gobo effect; strobe effect
- Color wheel with 8 dichroic filters plus open
half colors selectable, Rainbow effect with adjustable speed in both directions
- Gobo wheel with rotating gobos, 8 gobos
gobos changeable
- Slot-in gobo system for easy gobo replacement
- 24 integrated show programs
- The device is cooled by temperature-controlled fan
- Control via stand-alone; sound to light via microphone; master/slave function; DMX; IR remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Preprogrammed in Colorchief; Light Captain
- With a beam angle of 80°

- fitting; stage; mobile djs / entertainer; restaurants, bars and hotels
- Very quiet working noise
- Application possibility: Suspended; on stand
- 2 buttons on the remote control for saving your own settings

Package contents

1 x device, 1 x power cord, 1 x remote control, 1 x battery, 1 x user manual, 6 x gobos

4 digit 7-segment LED display Mains input and output for power linking up to 8 units For application areas such as: Clubs/dancing school; wedding/gala/events; Trade fair and shop

EUROLITE SB-16 Soft Bag

Universal softbag

- High-quality workmanship with nylon, black
- Interior with foam padding
- 2 carrying straps

Package contents

- 1 x bag

Technical specifications:

Weight: 5,68 kg

EUROLITE GoFlow 100

EUROLITE GUFIUW 100	
Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	140 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug
Power output:	IEC connector (F) mounting version
Fuse:	5 x 20 mm, T 2,5 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 100 W COB (chip-on-board) cold white (CW)
Flash rate:	0,5 - 25 Hz
Equipment:	Gobo wheel with rotating gobos; color wheel
Color generation:	Color wheel with 8 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed in both directions
Gobos:	Gobo wheel with rotating gobos, 8 gobos Outside diameter 23,80mm Image diameter 14mm Gobos changeable Slot-in gobo system for easy gobo replacement
DMX channels:	2; 6; 8
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	Stand-alone; sound to light via microphone; master/slave function; DMX; IR remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	Colorchief; Light Captain
Beam angle:	80°
Beam angle (1/2 peak):	80°

Color temperature:	8000K
Housing color:	Black
Display type:	4 digit 7-segment LED display
Dimensions:	Length: 40,5 cm
	Width: 22,5 cm
	Height: 26 cm
Weight:	5,40 kg
Noise classification:	Class 1 (very slight noise, suitable for noise- sensitive environments)
Remote control	
Battery:	Button cell 3.0 V CR2025 lithium manganese built- in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE SB-16 Soft Bag

Carrying strap:	2 pc/pcs
Material:	Nylon
Color:	Black
Dimensions:	Width: 44 cm
	Depth: 25 cm
	Height: 21,5 cm
Weight:	0,28 kg