



**List price: 2557.31 €**

incl. 19% VAT.

### Features:

#### EUROLITE Multiflood IP 8x10W RGBW Wash

Silent IP65 LED floodlight with RGBW color mixing, diffuser cover, barn doors and IR remote control

- Silent operation
- Control via stand-alone; DMX; Master/slave function; IR remote control; RDM
- Additional frost filter provides a wide, soft and homogeneous light
- 4 barn doors to avoid blinding the audience and for protection during transport
- 8 powerful LEDs 10 W high-power 4in1 QCL RGBW (homogenous color mix)
- 36 integrated show programs
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) with adjustable response; white balance
- Strobe effect
- 3 buttons on the remote control for saving your own settings
- With a beam angle of 10°
- With Mounting bracket; with Omega bracket
- OLED display
- Flicker-free
- Mains input and output for power linking up to 8 units
- Suitable for outdoor use IP65
- With pressure compensation membrane
- With a KENSINGTON LOCK theft protection
- For application areas such as: Stage; architecture; mobile use; Rental
- The device is cooled by passive convection cooling
- Preprogrammed in Light Captain; LED PC-Control 512; Light 'J
- Application possibility: Suspended; on stand; standing

#### Package contents

### Logistic

EAN / GTIN: 4026397527698

Weight: 55,50 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

Bulky product

- 1 x device, 1 x user manual, 1 x power cord, 1 x remote control, 1 x diffusor cover, 1 x omega bracket, 1 x barndoor, 1 x battery

### ROADINGER Flightcase 4x Multiflood IP 8x10W RGBW Wash

Trunk case with castors

- Interior with foam padding
- Aluminum profile frames 35mm with rounded edges
- 4 hinged, chromium plated case handles
- Edge mounting handle
- 3 chrome tip-over locks
- 2 high-quality butterfly locks
- 2 castors with 2 locking brakes
- 4 built-in stacking trays in the cover

### Technical specifications:

---

Weight: 54,30 kg

---

### EUROLITE Multiflood IP 8x10W RGBW Wash

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	80 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug (provided)
Power output:	IP T-Con (F) mounting version
Lamp type:	LED lamp
LED:	8 x 10 W high-power 4in1 QCL RGBW (homogenous color mix)
Flash rate:	1 - 23 Hz
DMX channels:	3; 4; 6; 8; 11
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; Master/slave function; IR remote control; RDM
Preprogrammed in:	Light Captain; LED PC-Control 512; Light 'J
Projection:	Flicker-free
Beam angle:	10°
Beam angle (1/2 peak):	10° Frost filter 25°
Beam angle (1/10 peak):	25° Frost filter 55°
Housing color:	Black
Attachment system:	Mounting bracket Omega bracket

---

Display type:	OLED display
Theft protection:	KENSINGTON LOCK
Dimensions:	Length: 31,9 cm Width: 14 cm Height: 24,8 cm
Weight:	6,10 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x Button cell 3.0 V CR2032 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

#### **ROADINGER Flightcase 4x Multiflood IP 8x10W RGBW Wash**

Aluminum profile frames:	35 mm
Case handle:	4 pc/pcs
Edge mounting handle:	1 pc/pcs
Stop hinge:	3 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	2 x castors with 2 locking brakes 4 x built-in stacking trays in the cover
Color:	Black, laminated
Device compartment:	15 cm x 46 cm x 30 cm
Accessory compartment:	8,5 cm x 46 cm x 30 cm
Material thickness:	9 mm
Dimensions:	Width: 87,5 cm Depth: 53 cm Height: 55,5 cm
Weight:	25,75 kg