

EUROLITE Set 16x LED Silent Par 6 QCL floor wh + Case

Art. No.: 20001003

GTIN: 4026397687088















List price: 4044.81 €

incl. 19% VAT.

Features:

EUROLITE LED Silent Par 6 QCL Floor wh

LED floor spot with RGB/WW color mixing

- 14350 lux at 1 m
- 6 powerful LEDs 8 W 4in1 QCL RGB/WW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic;
 Dimmer speed (step response) adjustable
- Strobe effect
- Direct color selection for 25 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; QuickDMX via USB (optional); master/slave function; sound to light via microphone
- Flicker-free
- With a beam angle of 16°
- With mounting bracket; with double bracket
- 4 digit 7-segment LED display
- Preprogrammed in Light'J; Light Captain; Colorchief
- For application areas such as: Clubs/dancing school; wedding/gala/events; Trade fair and shop fitting; stage; theater; restaurants, bars and hotels; mobile djs / entertainer
- Silent operation
- Application possibility: Standing; suspended; on stand

Package contents

- 1 x spotlight, 1 x power cord, 1 x user manual, 1 x XLR cable

ROADINGER Flightcase BAS-1 8x SILENT PAR 6 QCL FLOOR

Trunk case with castors, PRO version

Logistic

EAN / GTIN: 4026397687088

Weight: 80,00 kg Length: 0.00 m Width: 0.00 m Heigth: 0.00 m Bulky product

- High-quality workmanship with birch multiplex 10 mm, black, laminated
- Interior with felt cover
cover with foam padding
- Aluminum profile frames 32mm with rounded edges
- 4 hinged, chromium plated case handles
- 4 high-quality butterfly locks
- 4 castors with 2 locking brakes
- Branded hardware
- 2 Edge mounting handles
- 4 built-in stacking trays in the cover
- Made in Europe

ROADINGER Flightcase Extension 8x SILENT PAR 6 QCL FLOOR for BAS-1

- High-quality workmanship with birch multiplex 10 mm, black
- Interior with felt cover
cover with foam padding
- 4 hinged, chromium plated case handles
- 4 high-quality butterfly locks
- Branded hardware
- Made in Europe

Technical specifications:

Weight: 76,58 kg

EUROLITE LED Silent Par 6 QCL Floor wh

Power consumption: IP classification: IP classification: Protection class: Protection class: Power connection: Mains input via P-Con (blue), mounting version power supply cord with safety plug Power output: P-Con (gray), mounting version LED type: 6 x 8 W 4in1 QCL RGB/WW (homogenous color mix) Flash rate: 0 - 20 Hz DMX channels: 6; 11 DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Cooling: Passive convection cooling Control: Stand-alone; DMX; QuickDMX via USB (optional); master/slave function; sound to light via microphone Preprogrammed in: Light' J; Light Captain; Colorchief Projection: Flicker-free Beam angle: 16° Beam angle (1/2 peak): 16° Beam angle (1/10 peak): 29° Housing color: White	Power supply:	100-240 V AC, 50/60 Hz
Protection class: Protection class I Power connection: Mains input via P-Con (blue), mounting version power supply cord with safety plug Power output: P-Con (gray), mounting version EED type: 6 x 8 W 4in1 QCL RGB/WW (homogenous color mix) Flash rate: 0 - 20 Hz DMX channels: 6; 11 DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Cooling: Passive convection cooling Control: Stand-alone; DMX; QuickDMX via USB (optional); master/slave function; sound to light via microphone Preprogrammed in: Light'J; Light Captain; Colorchief Projection: Flicker-free Beam angle: 16° Beam angle (1/2 peak): 16° Beam angle (1/10 peak): 29°	Power consumption:	45 W
Power connection: Mains input via P-Con (blue), mounting version power supply cord with safety plug Power output: P-Con (gray), mounting version EED type: 6 x 8 W 4in1 QCL RGB/WW (homogenous color mix) Flash rate: 0 - 20 Hz DMX channels: 6; 11 DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Cooling: Passive convection cooling Control: Stand-alone; DMX; QuickDMX via USB (optional); master/slave function; sound to light via microphone Preprogrammed in: Light'J; Light Captain; Colorchief Projection: Flicker-free Beam angle: 16° Beam angle (1/12 peak): 16° Beam angle (1/10 peak): 29°	IP classification:	IP20
Power output: P-Con (gray), mounting version LED type: 6 x 8 W 4in1 QCL RGB/WW (homogenous color mix) Flash rate: 0 - 20 Hz DMX channels: 6; 11 DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Cooling: Passive convection cooling Control: Stand-alone; DMX; QuickDMX via USB (optional); master/slave function; sound to light via microphone Preprogrammed in: Light'J; Light Captain; Colorchief Projection: Flicker-free Beam angle: 16° Beam angle (1/2 peak): 16° Beam angle (1/10 peak): 29°	Protection class:	Protection class I
LED type: 6 x 8 W 4in1 QCL RGB/WW (homogenous color mix) Flash rate: 0 - 20 Hz DMX channels: 6; 11 DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Cooling: Passive convection cooling Control: Stand-alone; DMX; QuickDMX via USB (optional); master/slave function; sound to light via microphone Preprogrammed in: Light'J; Light Captain; Colorchief Projection: Flicker-free Beam angle: 16° Beam angle (1/2 peak): 16° Beam angle (1/10 peak): 29°	Power connection:	
Flash rate: 0 - 20 Hz DMX channels: 6; 11 DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Cooling: Passive convection cooling Control: Stand-alone; DMX; QuickDMX via USB (optional); master/slave function; sound to light via microphone Preprogrammed in: Light'J; Light Captain; Colorchief Projection: Flicker-free Beam angle: 16° Beam angle (1/2 peak): 16° Beam angle (1/10 peak): 29°	Power output:	P-Con (gray), mounting version
DMX channels: 6; 11 DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Cooling: Passive convection cooling Control: Stand-alone; DMX; QuickDMX via USB (optional); master/slave function; sound to light via microphone Preprogrammed in: Light´J; Light Captain; Colorchief Projection: Flicker-free Beam angle: 16° Beam angle (1/2 peak): 16° Beam angle (1/10 peak): 29°	LED type:	· · ·
DMX input: 3-pin XLR (M) mounting version 3-pin XLR (F) mounting version Cooling: Passive convection cooling Control: Stand-alone; DMX; QuickDMX via USB (optional); master/slave function; sound to light via microphone Preprogrammed in: Light´J; Light Captain; Colorchief Projection: Flicker-free Beam angle: 16° Beam angle (1/2 peak): 16° Beam angle (1/10 peak): 29°	Flash rate:	0 - 20 Hz
DMX output: 3-pin XLR (F) mounting version Passive convection cooling Control: Stand-alone; DMX; QuickDMX via USB (optional); master/slave function; sound to light via microphone Preprogrammed in: Light´J; Light Captain; Colorchief Projection: Flicker-free Beam angle: 16° Beam angle (1/2 peak): 16° Beam angle (1/10 peak): 29°	DMX channels:	6; 11
Cooling: Passive convection cooling Control: Stand-alone; DMX; QuickDMX via USB (optional); master/slave function; sound to light via microphone Preprogrammed in: Light'J; Light Captain; Colorchief Projection: Flicker-free Beam angle: 16° Beam angle (1/2 peak): 16° Beam angle (1/10 peak): 29°	DMX input:	3-pin XLR (M) mounting version
Control: Stand-alone; DMX; QuickDMX via USB (optional); master/slave function; sound to light via microphone Preprogrammed in: Light´J; Light Captain; Colorchief Projection: Flicker-free Beam angle: 16° Beam angle (1/2 peak): 16° Beam angle (1/10 peak): 29°	DMX output:	3-pin XLR (F) mounting version
master/slave function; sound to light via microphone Preprogrammed in: Light'J; Light Captain; Colorchief Projection: Flicker-free Beam angle: 16° Beam angle (1/2 peak): 16° Beam angle (1/10 peak): 29°	Cooling:	Passive convection cooling
Projection: Beam angle: 16° Beam angle (1/2 peak): 16° Beam angle (1/10 peak): 29°	Control:	master/slave function; sound to light via
Beam angle: 16° Beam angle (1/2 peak): 16° Beam angle (1/10 peak): 29°	Preprogrammed in:	Light´J; Light Captain; Colorchief
Beam angle (1/2 peak): 16° Beam angle (1/10 peak): 29°	Projection:	Flicker-free
Beam angle (1/10 peak): 29°	Beam angle:	16°
	Beam angle (1/2 peak):	16°
Housing color: White	Beam angle (1/10 peak):	29°
	Housing color:	White

Attachment system:	Mounting bracket
	Double bracket
	Double bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Length: 14,5 cm
	Width: 18,0 cm
	Height: 20,5 cm
Weight:	2,15 kg
Noise classification:	Class 0 (no noise at all)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase BAS-1 8x SILENT PAR 6 QCL FLOOR

Aluminum profile frames:	32 mm
Case handle:	4 pc/pcs
Edge mounting handle:	2 pc/pcs
Lock:	Butterfly lock: 4 pc/pcs
Transport aid:	4 x castors with 2 locking brakes 4 x built-in stacking trays in the cover
Use of brands:	Branded hardware
Material:	Birch multiplex, 10 mm
Color:	Black, laminated
Device compartment:	14,5 cm x 15 cm x 19 cm
Accessory compartment:	65,5 cm x 11 cm x 19 cm
Dimensions:	Length: 70 cm
	Width: 48 cm
	Height: 43,5 cm
Weight:	23,75 kg

ROADINGER Flightcase Extension 8x SILENT PAR 6 QCL FLOOR for BAS-1

Case handle:	4 pc/pcs
Lock:	Butterfly lock: 4 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 10 mm
Color:	Black
Device compartment:	14,5 cm x 15 cm x 16 cm
Accessory compartment:	66 cm x 11,5 cm x 16 cm
Dimensions:	Length: 69 cm
	Width: 47 cm
	Height: 29 cm
Weight:	13,40 kg