

FUTURELIGHT Set 4x EYE-740 MK2 + Case with wheels

Art. No.: 20001009

GTIN: 4026397695748



List price: on demand €

incl. 19% VAT.

Features:

FUTURELIGHT EYE-740 MK2 QCL Zoom LED Moving Head Wash

PRO Washlight with 40 W Osram Ostar RGBW LEDs, large zoom range and pixel control

- 7 powerful LEDs 40 W 4in1 QCL RGBW (homogenous color mix)
 LEDs controlled separately
- Compact lightweight
- Variable color temperature 2800 K - 10000 K
- Crossfade channel from any color to white
- Number of scenes can be changed individually
- Positioning within 540° PAN, 210° TILT
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Exact 16 bit resolution at Dimmer, color, zoom
- The device is cooled by temperature-controlled fan
- Control via stand-alone; master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); CRMX by LumenRadio upgradeable; RDM; sound to light via microphone
- Flicker-free
- With a beam angle of 1° - 48°
- Multicolor LCD display,
with battery buffering for easy controlling upgradeable
- Zoom motor driven
- Patterns animated; foreground color adjustable; background color adjustable; dimmer curves with adjustable response; pulse-width modulation variable; pulse effect adjustable; white balance; scenes user-definable; CTO correction filter virtual; Dim to warm; colors preset; Dimmer speed (step response) adjustable
- Strobe effect
- Very quiet working noise

Logistic

EAN / GTIN: 4026397695748

Weight: 78,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

Bulky product

- OSRAM LED installed
 - Preprogrammed in Light Captain
 - With omega bracket
 - Rubber feet
 - Mains input and output for power linking up to 8 units
 - For application areas such as: Wedding/gala/events; stage; theater; rental
 - Application possibility: Standing; suspended
- Package contents**
- 1 x moving light, 1 x user manual, 1 x power cord, 1 x omega bracket, 1 x XLR cable

ROADINGER Flightcase 4x EYE-740 MK2 with wheels

Trunk case with castors

- With 4 device compartments
- With 1 accessory compartment
- High-quality workmanship with plywood multi-layer glued 7 mm, black, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- 4 hinged, chromium plated case handles
- 3 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 castors with 2 locking brakes

Technical specifications:

| | |
|---------|----------|
| Weight: | 76,90 kg |
|---------|----------|

FUTURELIGHT EYE-740 MK2 QCL Zoom LED Moving Head Wash

| | |
|---------------------|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 210 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Mains input via IP T-Con (M) mounting version power supply cord with safety plug |
| Power output: | IP T-Con (F) mounting version |
| Device fuse: | 5 x 20 mm, T 2 A fuse replaceable |
| Lamp type: | LED lamp |
| LED type: | 7 x 40 W 4in1 QCL RGBW (homogenous color mix) |
| LED manufacturer: | OSRAM |
| Max. TILT movement: | 210° exact positioning (16 bit resolution) auto position correction (feedback) |
| Max. PAN movement: | 540° exact positioning (16 bit resolution) auto position correction (feedback) |
| Flash rate: | 0,5 - 16 Hz |
| Equipment: | Zoom motor driven |
| DMX channels: | 18; 25; 37; 26; 33; 45; 46; 53; 65 |
| DMX input: | 3-pin XLR (M) mounting version 5-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |

| | |
|--------------------------|--|
| | 5-pin XLR (F) mounting version |
| Cooling: | Temperature-controlled fan |
| Control: | Stand-alone; master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); CRMX by LumenRadio upgradeable; RDM; sound to light via microphone |
| Preprogrammed in: | Light Captain |
| Projection: | Flicker-free |
| Beam angle: | 1° - 48° |
| Beam angle (1/2 peak): | 1 - 32° |
| Beam angle (1/10 peak): | 5 - 48° |
| Color temperature: | 2800K - 10000K adjustable |
| Illuminance in Lux (lx): | Narrow red (R) 3m: 6818 lx, 6m: 1758 lx Narrow green (G) 3m: 12807 lx, 6m: 3122 lx Narrow blue (B) 3m: 2513 lx, 6m: 21580 lx Narrow cold white (CW) 3m: 21580 lx, 6m: 5431 lx Narrow all 3m: 38576 lx, 6m: 9662 lx Wide red (R) 3m: 162 lx, 6m: 46 lx Wide green (G) 3m: 315 lx, 6m: 89 lx Wide blue (B) 3m: 85 lx, 6m: 25 lx Wide cold white (CW) 3m: 504 lx, 6m: 143 lx Wide all 3m: 915 lx, 6m: 259 lx |
| Housing color: | Black |
| Attachment system: | Omega bracket |
| Display type: | Multicolor LCD display battery buffering upgradeable |
| Transport aid: | Rubber feet |
| Dimensions: | Width: 28,6 cm Depth: 24,5 cm Height: 37,2 cm |
| Weight: | 8,10 kg |
| Noise classification: | Class 1 (very slight noise, suitable for noise-sensitive environments) |

ROADINGER Flightcase 4x EYE-740 MK2 with wheels

| | |
|--------------------------|-----------------------------------|
| Maximum load: | 100 kg |
| Aluminum profile frames: | 30 mm |
| Case handle: | 4 pc/pcs |
| Stop hinge: | 3 pc/pcs |
| Lock: | Butterfly lock: 2 pc/pcs |
| Transport aid: | 4 x castors with 2 locking brakes |
| Material: | Plywood multi-layer glued, 7 mm |
| Color: | Black, laminated |
| Inside dimensions: | 81 cm x 53,5 cm x 36,5 cm |
| Device compartment: | 28 cm x 17,5 cm x 36,5 cm |

| | |
|------------------------|---------------------------|
| Accessory compartment: | 10,5 cm x 53,5 cm x 36 cm |
| Dimensions: | Width: 87 cm |
| | Depth: 60 cm |
| | Height: 63 cm |
| Weight: | 39,35 kg |