



**List price: 3568.81 €**

incl. 19% VAT.

### Features:

#### EUROLITE LED TMH-X4 Moving Head Wash Zoom

Washlight with 19 x 15 W LEDs, 4in1 QCL RGBW-Farbmischung and motorized zoom

- 19 powerful LEDs 15 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix) <BR>3 segments controlled separately
- Positioning within 540° PAN and 270° TILT
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Zoom motor-driven
- Integrated show programs
- The device is cooled by temperature-controlled fan at the Head; cooling fan at the Base
- Control via stand-alone; DMX; Sound to light via Microphone; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 1° - 40°
- Multicolor LCD display
- Color blend stepless; color change adjustable; Dimmer electronic
- Strobe effect
- Preprogrammed in Light´J; LED PC-Control 512; EASY SHOW 1; Light Captain
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; Wedding/gala/events; Stage; mobile djs / entertainer; Rental
- Application possibility: Standing; suspended

#### Package contents

- 1 x moving light, 1 x user manual, 1 x power cord, 2 x omega bracket

### Logistic

EAN / GTIN: 4026397702354

Weight: 60,50 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

Bulky product

## ROADINGER Flightcase 4x TMH-X4

### Trunk case

- Interior with foam padding<BR>cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 castors with 2 locking brakes

## Technical specifications:

---

Weight: 59,85 kg

---

## EUROLITE LED TMH-X4 Moving Head Wash Zoom

|                          |   |
|--------------------------|---|
| Power supply:            | 100-240 V AC, 50/60 Hz  |
| Power consumption:       | 225 W   |
| IP classification:       | IP20  |
| Power connection:        | Mains input via P-Con (blue), mounting version<br>power supply cord with safety plug  |
| Power output:            | P-Con (gray), mounting version  |
| Fuse:                    | 5 x 20 mm, T 2 A Fuse replaceable   |
| Lamp type:               | LED lamp  |
| LED:                     | 19 x 15 W COB (chip-on-board) 4in1 QCL RGBW<br>(homogenous color mix)   |
| Max. TILT movement:      | 270° Exact positioning (16 bit resolution) Auto<br>position correction (feedback)   |
| Max. PAN movement:       | 540° Exact positioning (16 bit resolution) Auto<br>position correction (feedback)   |
| Equipment:               | Zoom motor-driven   |
| DMX channels:            | 16; 24  |
| DMX input:               | 3-pin XLR (M) mounting version  |
| DMX output:              | 3-pin XLR (F) mounting version  |
| Cooling:                 | Temperature-controlled fan at the Head<br>Cooling fan at the Base   |
| Control:                 | Stand-alone; DMX; Sound to light via<br>Microphone; Master/slave function; QuickDMX via<br>USB (optional); W-DMX by wireless solution via<br>USB (optional); CRMX by LumenRadio via USB<br>(optional) |
| Preprogrammed in:        | Light J; LED PC-Control 512; EASY SHOW 1;<br>Light Captain  |
| Projection:              | Flicker-free  |
| Beam angle:              | 1° - 40°  |
| Beam angle (1/2 peak):   | 1 - 25°   |
| Beam angle (1/10 peak):  | 8 - 40°   |
| Illuminance in Lux (lx): | Narrow red (R) 3m: 2779 lx, 6m: 763 lx  |

Narrow green (G) 3m: 7893 lx, 6m: 1841 lx  
Narrow blue (B) 3m: 1468 lx, 6m: 390 lx  
Narrow cold white (CW) 3m: 9558 lx, 6m: 2468 lx  
Narrow all 3m: 19553 lx, 6m: 5001 lx  
Wide red (R) 3m: 272 lx, 6m: 73 lx  
Wide green (G) 3m: 583 lx, 6m: 160 lx  
Wide blue (B) 3m: 117 lx, 6m: 34 lx  
Wide cold white (CW) 3m: 740 lx, 6m: 211 lx  
Wide all 3m: 1568 lx, 6m: 439 lx

|                         |   |
|-------------------------|---|
| Housing color:          | Black   |
| Display type:           | Multicolor LCD display                              |
| Dimensions:             | Width: 30,5 cm<br>Depth: 20,0 cm<br>Height: 40,0 cm |
| Weight:                 | 8,62 kg   |
| Noise classification:   | Class 3 (clearly perceptible sounds)                |
| Photobiological safety: | Risk Group 0  |
| Legal specifications    |   |
| Special product:        | Not designed for household room illumination        |
| Intended use:           | Show effect lighting                                |

#### **ROADINGER Flightcase 4x TMH-X4**

|                          |   |
|--------------------------|---|
| Maximum load:            | 100 kg  |
| Aluminum profile frames: | 30 mm   |
| Case handle:             | 4 pc/pcs                                      |
| Stop hinge:              | 2 pc/pcs                                      |
| Lock:                    | Butterfly lock: 2 pc/pcs                      |
| Transport aid:           | 4 x castors with 2 locking brakes             |
| Material:                | Plywood multi-layer glued                     |
| Color:                   | Black, laminated                              |
| Inside dimensions:       | 74 cm x 47 cm x 40 cm                         |
| Device compartment:      | 32 cm x 23 cm x 40 cm                         |
| Accessory compartment:   | 8 cm x 47 cm x 24 cm                          |
| Dimensions:              | Width: 80 cm<br>Depth: 53 cm<br>Height: 55 cm |
| Weight:                  | 21,50 kg                                      |