
eurolite®

EUROLITE Set 4x LED TMH-X4 white + Case with wheels

Art. No.: 20001016 GTIN: 4026397702668







incl. 19% VAT.

Features:

EUROLITE LED TMH-X4 Moving Head Wash Zoom wh

Washlight with 19 intense 15 W 4in1 LEDs, motorized zoom and white housing

- 19 powerful LEDs 15 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
3 segments controlled separately
- Positioning within 630° PAN, 270° TILT
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Zoom motor driven
- Integrated show programs
- The device is cooled by temperature-controlled fan at the Head; cooling fan at the base
- Control via stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 1° 40°
- Multicolor LCD display
- Color blend stepless; color change adjustable; Dimmer electronic
- Strobe effect
- Preprogrammed in Light'J; LED PC-Control 512; EASY SHOW 1; Light Captain
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; wedding/gala/events; stage; mobile djs / entertainer; rental
- Application possibility: Standing; suspended
- Package contents
- 1 x moving light, 1 x user manual, 1 x power cord, 2 x omega bracket

Logistic

EAN / GTIN: 4026397702668 Weight: 60,50 kg Length: 0.00 m Width: 0.00 m Heigth: 0.00 m Bulky product

ROADINGER Flightcase 4x TMH-X4

Trunk case

- Interior with foam padding
cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 castors with 2 locking brakes
- With 4 device compartments
- With 1 accessory compartment
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:

59,85 kg

EUROLITE LED TMH-X4 Moving Head Wash Zoom wh

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	225 W
IP classification:	IP20
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Power output:	P-Con (gray), mounting version
Fuse:	5 x 20 mm, T 2 A fuse replaceable
Lamp type:	LED lamp
LED type:	19 x 15 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
Max. TILT movement:	270° exact positioning (16 bit resolution) auto position correction (feedback)
Max. PAN movement:	630° exact positioning (16 bit resolution) auto position correction (feedback)
Equipment:	Zoom motor driven
DMX channels:	16; 24
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan at the Head Cooling fan at the base
Control:	Stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	Light J; LED PC-Control 512; EASY SHOW 1; Light Captain
Projection:	Flicker-free
Beam angle:	1° - 40°
Beam angle (1/2 peak):	1 - 25°

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

6m: 763 lx
x, 6m: 1841 lx
6m: 390 lx
9558 lx, 6m: 2468 lx
5001 lx
73 lx
m: 160 lx
: 34 lx
0 lx, 6m: 211 lx
) Ix
ounds)
oom illumination

ROADINGER Flightcase 4x TMH-X4

Maximum load:	100 kg
Aluminum profile frames:	30 mm
Case handle:	4 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes
Material:	Plywood multi-layer glued
Color:	Black, laminated
Inside dimensions:	74 cm x 47 cm x 40 cm
Device compartment:	32 cm x 23 cm x 40 cm
Accessory compartment:	8 cm x 47 cm x 24 cm
Dimensions:	Width: 80 cm
	Depth: 53 cm
	Height: 55 cm
Weight:	21,50 kg