

List price: 5472.81 €

incl. 19% VAT.

Features:

EUROLITE LED IP TMH-H760 Beam/Wash/Flower Effect

Powerful weather-proof moving washlight with 19x 40W RGBW LEDs, rotating flower effect and pixel control

- 19 powerful LEDs 40 W SMD 4in1 QCL RGBW (homogenous color mix)
 LEDs controlled separately
- Positioning within 540° PAN, 210° TILT
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Zoom motor driven rotating; lens rotation
- Flower effect; strobe effect; wash effect
- With a beam angle of 2° - 30°
- With bracket with hinged hooks
- Multicolor LCD display
- The device is cooled by temperature-controlled fan at the Head; cooling fan at the base
- For application areas such as: Stage; rental
- Application possibility: Standing; suspended
- Color blend stepless; colors preset; pulse-width modulation
- Control via stand-alone; DMX; master/slave function
- Flicker-free
- DMX fail mode (hold; zero values)
- 2 Rugged carrying handles
- 4 rubber feet
- Mains input and output for power linking up to 3 units
- Built with SEETRONIC connector
- Suitable for outdoor use IP65
- With pressure compensation membrane
- Very quiet working noise

Logistic

EAN / GTIN: 4026397684117

Package contents

- 1 x moving light, 1 x user manual, 1 x power cord, 1 x XLR cable

ROADINGER Flightcase 2x IP TMH-H760 with wheels

Trunk case with castors

- Interior with foam padding
cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks with shut-off function
- 4 castors with 2 locking brakes
- 4 built-in stacking trays in the cover
- With 2 device compartments
- With 1 accessory compartment
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	77,50 kg
---------	----------

EUROLITE LED IP TMH-H760 Beam/Wash/Flower Effect

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	780 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) power supply cord with safety plug
Cable construction:	3 x 1,5 mm ² H07RN-F
Power output:	IP T-Con (F) mounting version
Fuse:	5 x 20 mm, T 8 A fuse replaceable
Lamp type:	LED lamp
LED type:	19 x 40 W SMD 4in1 QCL RGBW (homogenous color mix)
Max. TILT movement:	210° exact positioning (16 bit resolution) auto position correction (feedback)
Max. PAN movement:	540° exact positioning (16 bit resolution) auto position correction (feedback)
Flash rate:	1 - 20 Hz
Equipment:	Zoom motor driven rotating; lens rotation
DMX channels:	18; 30; 94
DMX input:	3-pin XLR (M) mounting version IP 5-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP 5-pin XLR (F) mounting version IP
Cooling:	2 x temperature-controlled fan at the Head 2 x cooling fan at the base
Control:	Stand-alone; DMX; master/slave function

Projection:	Flicker-free
DMX fail mode:	Hold; zero values
Beam angle:	2° - 30°
Beam angle (1/2 peak):	2 - 16°
Beam angle (1/10 peak):	7 - 30°
Illuminance in Lux (lx):	<p>Narrow red (R) 1m: 13602 lx, 3m: 11354 lx, 6m: 4333 lx</p> <p>Narrow green (G) 1m: 31916 lx, 3m: 29390 lx, 6m: 9454 lx</p> <p>Narrow blue (B) 1m: 3891 lx, 3m: 3565 lx, 6m: 1777 lx</p> <p>Narrow cold white (CW) 1m: 52981 lx, 3m: 45405 lx, 6m: 14131 lx</p> <p>Narrow all 3m: 78579 lx, 6m: 27552 lx</p> <p>Wide red (R) 1m: 9199 lx, 3m: 1243 lx, 6m: 336 lx</p> <p>Wide green (G) 1m: 19373 lx, 3m: 2700 lx, 6m: 736 lx</p> <p>Wide blue (B) 1m: 2768 lx, 3m: 575 lx, 6m: 163 lx</p> <p>Wide cold white (CW) 1m: 29680 lx, 3m: 4088 lx, 6m: 1109 lx</p> <p>Wide all 1m: 56588 lx, 3m: 8061 lx, 6m: 2192 lx</p>
Lamp life:	10000 h
Housing color:	Black
Attachment system:	<p>Ø 50 mm</p> <p>2x bracket with hinged hooks</p>
Display type:	Multicolor LCD display
Carrying handle:	2 pc/pcs
Transport aid:	4 x rubber feet
Use of brands:	Built with SEETRONIC connector
Material:	Aluminum casting
Dimensions:	<p>Width: 41,0 cm</p> <p>Depth: 24 cm</p> <p>Height: 55,5 cm</p>
Weight:	24,60 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments) depending on mode used; class 3 (clearly perceptible sounds)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 2x IP TMH-H760 with wheels

Maximum load:	100 kg
Aluminum profile frames:	30 mm
Case handle:	4 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs with shut-off function
Transport aid:	<p>4 x castors with 2 locking brakes</p> <p>4 x built-in stacking trays in the cover</p>

Material:	Plywood multi-layer glued
Color:	Black, laminated
Device compartment:	39 cm x 42 cm x 61 cm
Accessory compartment:	8 cm x 42 cm x 24 cm
Inside dimensions:	90 cm x 42 cm x 61 cm
Dimensions:	Width: 95 cm Depth: 47 cm Height: 80 cm
Weight:	28,30 kg