

## EUROLITE Set LED TMH Bar S120 + Soft Bag

Art. No.: 20001022

GTIN: 4026397739428



### Features:

#### EUROLITE LED TMH Bar S120 Moving Head Spots

LED lighting system with 4 individually controllable 30 W moving heads

- Crossbar with integrated DMX control unit and stand sleeve
- 4 LEDs 30 W COB (chip-on-board)
- Positioning within 540° PAN, 180° TILT
- Exact positioning (16 bit resolution)
- Gobo wheel with static gobos; focus manual; color wheel
- Dimmer electronic
- Strobe effect; beam effect
- Color wheel with 7 dichroic filters plus open<BR>half colors selectable, Rainbow effect with adjustable speed
- Gobo wheel with static gobos, 7 gobos and open<BR>shake effect
- The device is cooled by temperature-controlled fan
- Control via stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional)
- Fixtures available for Colorchief; Light´J; Light Captain
- Flicker-free
- With a beam angle of 13°
- With omega bracket
- 4 digit 7-segment LED display
- Rubber feet
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; wedding/gala/events; party room; mobile djs / entertainer; restaurants, bars and hotels
- Application possibility: Standing; suspended; on stand

### Logistic

EAN / GTIN: 4026397739428

Weight: 20,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

## EUROLITE Soft Bag for LED TMH Bar

Transport bag

- With accessory pocket in the cover
- Interior with foam padding<BR>cover with foam padding
- 2 carrying straps

## Technical specifications:

---

|         |          |
|---------|----------|
| Weight: | 14.99 kg |
|---------|----------|

---

## EUROLITE LED TMH Bar S120 Moving Head Spots

|                         |                                                                                                                                                                                                       |
|-------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply:           | 100-240 V AC, 50/60 Hz                                                                                                                                                                                |
| Power consumption:      | 100 W                                                                                                                                                                                                 |
| IP classification:      | IP20                                                                                                                                                                                                  |
| Protection class:       | Protection class I                                                                                                                                                                                    |
| Power connection:       | Mains input via P-Con (blue), mounting version<br>power supply cord with safety plug (provided)                                                                                                       |
| Power output:           | P-Con (gray), mounting version                                                                                                                                                                        |
| Fuse:                   | 5 x 20 mm, T 2 A fuse replaceable                                                                                                                                                                     |
| Lamp type:              | LED lamp                                                                                                                                                                                              |
| LED type:               | 4 x 30 W COB (chip-on-board)                                                                                                                                                                          |
| Max. TILT movement:     | 180° positioning; exact positioning (16 bit<br>resolution)                                                                                                                                            |
| Max. PAN movement:      | 540° positioning; exact positioning (16 bit<br>resolution)                                                                                                                                            |
| Flash rate:             | 2 - 14 Hz                                                                                                                                                                                             |
| Equipment:              | Gobo wheel with static gobos; focus manual;<br>color wheel                                                                                                                                            |
| Color generation:       | Color wheel with 7 dichroic filters plus open<br>Half colors selectable, Rainbow effect with<br>adjustable speed                                                                                      |
| Gobos:                  | Gobo wheel with static gobos, 7 gobos and open<br>Shake effect                                                                                                                                        |
| DMX channels:           | 3; 5; 9; 11; 17; 21; 30; 38                                                                                                                                                                           |
| DMX input:              | 3-pin XLR (M) mounting version                                                                                                                                                                        |
| DMX output:             | 3-pin XLR (F) mounting version                                                                                                                                                                        |
| Cooling:                | Temperature-controlled fan                                                                                                                                                                            |
| Control:                | Stand-alone; DMX; sound to light via microphone;<br>master/slave function; QuickDMX via USB<br>(optional); CRMX by LumenRadio via USB<br>(optional); W-DMX by wireless solution via USB<br>(optional) |
| Fixtures available for: | Colorchief; Light´J; Light Captain                                                                                                                                                                    |
| Projection:             | Flicker-free                                                                                                                                                                                          |
| PWM frequency:          | 11000 Hz                                                                                                                                                                                              |

|                          |                                                      |
|--------------------------|------------------------------------------------------|
| Beam angle:              | 13°                                                  |
| Beam angle (1/2 peak):   | 13°                                                  |
| Color temperature:       | 7300K                                                |
| Illuminance in Lux (lx): | Cold white (CW) 1m: 8899 lx, 3m: 856 lx, 6m: 205 lx  |
| Housing color:           | Black                                                |
| Attachment system:       | 2x omega bracket<br>Tube: Ø 35mm                     |
| Display type:            | 4 digit 7-segment LED display                        |
| Transport aid:           | Rubber feet                                          |
| Dimensions:              | Width: 100.0 cm<br>Depth: 17.5 cm<br>Height: 28.0 cm |
| Weight:                  | 13.00 kg                                             |
| Noise classification:    | Class 3 (clearly perceptible sounds)                 |
| Special product:         | Not designed for household room illumination         |
| Intended use:            | Show effect lighting                                 |

#### **EUROLITE Soft Bag for LED TMH Bar**

|                    |                                                   |
|--------------------|---------------------------------------------------|
| Maximum load:      | 25 kg                                             |
| Carrying strap:    | 2 pc/pcs                                          |
| Color:             | Black                                             |
| Inside dimensions: | 100 cm x 26 cm x 12 cm                            |
| Dimensions:        | Length: 114 cm<br>Width: 16.5 cm<br>Height: 38 cm |
| Weight:            | 1.99 kg                                           |

#### **Scope of delivery:**

1 x moving light  
 1 x user manual  
 1 x power cord  
 2 x omega bracket  
 2 x safety eyelet