



List price: 4223.31 €

incl. 19% VAT.

Features:

EUROLITE Multiflood IP 18x10W RGBW Wash CRMX

Silent IP65 LED floodlight with RGBW color mixing, CRMX, diffuser cover, barn doors, IR remote control

- Integrated wireless receiver for CRMX operation
- Silent operation
- Control via DMX; W-DMX by wireless solution; CRMX by LumenRadio; master/slave function; RDM; stand-alone; IR remote control
- Additional frost filter provides a wide, soft and homogeneous light
- 4 barn doors to avoid blinding the audience and for protection during transport
- 18 powerful LEDs 10 W high-power 4in1 QCL RGBW (homogenous color mix)
- 3 buttons on the remote control for saving your own settings
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) with adjustable response; white balance
- Direct color selection for 15 preset colors
- 36 integrated show programs
- Strobe effect
- Flicker-free
- With a beam angle of 10°
- With mounting bracket; with omega bracket
- OLED display
- Mains input and output for power linking up to 8 units
- Suitable for outdoor use
- With pressure compensation membrane
- With a KENSINGTON LOCK theft protection
- For application areas such as: Stage; architecture; mobile use; rental
- The device is cooled by passive convection cooling
- Application possibility: Suspended; on stand; standing

Logistic

EAN / GTIN: 4026397709605

Weight: 85,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

Bulky product

- Preprogrammed in Light´J; Light Captain; Colorchief

Package contents

- 1 x device, 1 x user manual, 1 x power cord, 1 x declaration of conformity, 1 x frost filter, 1 x barndoor, 1 x omega bracket, 1 x remote control

ROADINGER Flightcase 4x Multiflood IP 18x10W RGBW Wash CRMX with wheels

Trunk case with castors

- Interior with foam padding
cover with foam padding
- Aluminum profile frames 35mm with rounded edges
- 4 hinged, chromium plated case handles
- Edge mounting handle
- 3 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 castors with 2 locking brakes
- 4 built-in stacking trays in the cover
- Interior with foam padding
cover with foam padding
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

| | |
|---------|----------|
| Weight: | 80,00 kg |
|---------|----------|

EUROLITE Multiflood IP 18x10W RGBW Wash CRMX

| | |
|------------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 170 W |
| IP classification: | IP65 |
| Protection class: | Protection class I |
| Power connection: | Mains input via IP T-Con (M) mounting version power supply cord with safety plug |
| Power output: | 1 x IP T-Con (F) mounting version |
| Lamp type: | LED lamp |
| LED type: | 18 x 10 W high-power 4in1 QCL RGBW (homogenous color mix) |
| Flash rate: | 1 - 23 Hz |
| DMX channels: | 3; 4; 6; 8; 11 |
| DMX input: | 1 x 3-pin XLR (M) mounting version IP 1 x 5-pin XLR (M) mounting version IP |
| DMX output: | 1 x 3-pin XLR (F) mounting version IP 1 x 5-pin XLR (F) mounting version IP |
| Cooling: | Passive convection cooling |
| Control: | DMX; W-DMX by wireless solution; CRMX by LumenRadio; master/slave function; RDM; stand- alone; IR remote control |
| Preprogrammed in: | Light´J; Light Captain; Colorchief |
| Projection: | Flicker-free |
| Carrier frequency: | 2,4 GHz |
| Beam angle: | 10° |
| Beam angle (1/2 peak): | 10° |

| | |
|-------------------------|---|
| | Frost filter 20° |
| Beam angle (1/10 peak): | 25 |
| | Frost filter 50 |
| Housing color: | Black |
| Attachment system: | Mounting bracket Omega bracket |
| Display type: | OLED display |
| Theft protection: | KENSINGTON LOCK |
| Dimensions: | Length: 41 cm Width: 18,4 cm Height: 26,9 cm |
| Weight: | 10,00 kg |
| Noise classification: | Class 0 (no noise at all) |
| Remote control | |
| Battery: | 1 x button cell 3.0 V CR2032 lithium manganese built-in |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

ROADINGER Flightcase 4x Multiflood IP 18x10W RGBW Wash CRMX with wheels

| | |
|--------------------------|---|
| Aluminum profile frames: | 35 mm |
| Case handle: | 4 pc/pcs |
| Edge mounting handle: | 1 pc/pcs |
| Stop hinge: | 3 pc/pcs |
| Lock: | Butterfly lock: 2 pc/pcs |
| Transport aid: | 4 x castors with 2 locking brakes 4 x built-in stacking trays in the cover |
| Color: | Black, laminated |
| Device compartment: | 19 cm x 51 cm x 36 cm |
| Accessory compartment: | 11 cm x 51 cm x 36 cm |
| Material thickness: | 9 mm |
| Dimensions: | Width: 105 cm Depth: 57 cm Height: 57 cm |
| Weight: | 31,90 kg |