



List price: 2973.81 €

incl. 19% VAT.

Features:

EUROLITE AKKU IP Pixel Tube 360° PRO CRMX

Battery-powered IP pixel tube with RGB/CW/WW color mixing, 360° beam angle and CRMX receiver

- Integrated wireless receiver for CRMX operation
- Cordless, flexible and versatile
- Battery operation up to 8,5h depending on program used
- Integrated automatic charging of the battery and status indicator
- 144 powerful LEDs 0,5 W SMD 5050 5in1 PCL RGB/CW/WW (homogenous color mix)
24 segments controlled separately
- Dimmer electronic; Dimmer speed (step response) adjustable; color blend adjustable; color macros preset; white balance adjustable; program selection manual; running light automatic; background color adjustable; Emergency lighting function in case of power failure adjustable; Energy-saving mode
- 53 integrated show programs
- Direct color selection for 37 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; IR remote control; CRMX by LumenRadio
- Preprogrammed in Light Captain; Colorchief
- Flicker-free
- DMX fail mode (hold; blackout; static; full on)
- With a beam angle of 360°
- Good color rendering index (CRI)
- With holding clip
- Monochrome OLED display
- Charge status indicator
- Display of the remaining battery life for the current setting
- Suitable for outdoor use IP65

Logistic

EAN / GTIN: 4026397748147

Weight: 28,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

Bulky product

- With pressure compensation membrane
- With a KENSINGTON LOCK theft protection
- Application possibility: Standing; suspended
- 3 buttons on the remote control for saving your own settings

Package contents

- 1 x light effect, 1 x charger, 1 x power cord, 1 x remote control, 1 x battery, 1 x stand, 2 x fixation clip, 2 x splint, 1 x user manual, 1 x declaration of conformity, 1 x adapter

ROADINGER Plastic Case for 4x AKKU IP Pixel Tube 360° CRMX

Carrying case

- With accessory compartment
- With 4 device compartments
- Interior with foam padding
cover with foam padding
- 3 hinged, chromium plated case handles
- 1 Hinge strap
- 8 high-quality spring locks with shut-off function
- Trolley
- For application areas such as: Mobile use; wedding/gala/events; mobile djs / entertainer

Package contents

- 1 x case

Technical specifications:

| | |
|---------|----------|
| Weight: | 26,50 kg |
|---------|----------|

EUROLITE AKKU IP Pixel Tube 360° PRO CRMX

| | |
|---------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz 13V DC 3000 mA |
| IP classification: | IP65 |
| Protection class: | Protection class III |
| Power connection: | Mains input via coaxial power connector (M) power supply cord with AC unit (provided) Battery/battery pack |
| Cable construction: | 2 x 0,75 mm² H03VVH2-F |
| Battery pack type: | 1 x lithium ion 10,8 V, 9000 mAh, 97,2 Wh |
| Battery pack: | Battery operation up to 8,5h depending on program used Recharging time 4h |
| Lamp type: | LED lamp |
| LED type: | 144 x 0,5 W SMD 5050 5in1 PCL RGB/CW/WW (homogenous color mix) |
| Flash rate: | 2 - 20 Hz |
| DMX channels: | 4; 5; 7; 14; 16; 20,1; 20,2; 22,1; 22,2; 24,1; 24,2; 120; 124 |
| Cooling: | Passive convection cooling |
| Control: | Stand-alone; IR remote control; CRMX by LumenRadio |
| Preprogrammed in: | Light Captain; Colorchief |
| Projection: | Flicker-free |

| | |
|------------------------------|---|
| PWM frequency: | 12600 Hz |
| Carrier frequency: | 2,4 GHz |
| Modulation: | GFSK |
| DMX fail mode: | Hold; blackout; static; full on |
| Beam angle: | 360° |
| Beam angle (1/2 peak): | 360° |
| Beam angle (1/10 peak): | 360° |
| Color rendering index (CRI): | 84 Ra |
| Housing color: | Black matte |
| Attachment system: | 2x holding clip M10 thread |
| Display type: | Monochrome OLED display |
| Display: | Charge status indicator , battery runtime calculation |
| Material: | Plastic; aluminum |
| Theft protection: | KENSINGTON LOCK |
| Dimensions: | Length: 109 cm Width: 7,0 cm Depth: 7,0 cm |
| Weight: | 2,80 kg |
| Remote control | |
| Battery: | 1 x button cell 3.0 V CR2032 lithium manganese built-in |

ROADINGER Plastic Case for 4x AKKU IP Pixel Tube 360° CRMX

| | |
|---------------------|---|
| Maximum load: | 50 kg |
| Case handle: | 3 pc/pcs |
| Lock: | Spring lock: 8 pc/pcs with shut-off function |
| Transport aid: | Trolley |
| Material: | Plastic |
| Color: | Black |
| Device compartment: | 109 cm x 8 cm x 7,5 cm |
| Middle compartment: | 50 cm x 42 cm x 8 cm |
| Dimensions: | Length: 117,5 cm Depth: 52 cm Height: 21 cm |
| Weight: | 11,40 kg |