



8X



**List price: 5353.81 €**

incl. 19% VAT.

### Features:

#### EUROLITE AKKU IP Pixel Tube 360° PRO CRMX

Battery-powered IP pixel tube with RGB/CW/WW color mixing, 360° beam angle and CRMX receiver

- Integrated wireless receiver for CRMX operation
- Suitable for outdoor use IP65
- 144 powerful LEDs 0,5 W SMD 5050 5in1 PCL RGB/CW/WW (homogenous color mix)<BR>24 segments controlled separately
- Battery operation up to 8,5h depending on program used
- Integrated automatic charging of the battery and status indicator
- Dimmer electronic; Dimmer speed (step response) adjustable; color blend adjustable; color macros preset; white balance adjustable; program selection manual; running light automatic; background color adjustable; Emergency lighting function in case of power failure adjustable; Energy-saving mode
- Control via stand-alone; IR remote control; CRMX by LumenRadio
- DMX fail mode (hold; blackout; static; full on)
- With a beam angle of 360°
- Monochrome OLED display
- Charge status indicator
- Display of the remaining battery life for the current setting
- 3 buttons on the remote control for saving your own settings
- With pressure compensation membrane
- With holding clip
- With a KENSINGTON LOCK theft protection
- The device is cooled by passive convection cooling
- Application possibility: Standing; suspended
- Cordless, flexible and versatile
- 53 integrated show programs

### Logistic

EAN / GTIN: 4026397748154

Weight: 65,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

Bulky product

- Direct color selection for 37 preset colors
- Preprogrammed in Light Captain; Colorchief
- Flicker-free
- Good color rendering index (CRI)

#### Package contents

- 1 x light effect, 1 x charger, 1 x power cord, 1 x remote control, 1 x battery, 1 x stand, 2 x fixation clip, 2 x splint, 1 x user manual, 1 x declaration of conformity, 1 x adapter

### ROADINGER Flightcase 8x AKKU IP Pixel Tube 360° PRO CRMX with charging function and wheels

#### Trunk case

- Interior with foam padding<BR>cover with foam padding
- Aluminum profile frames 35mm with rounded edges
- 4 hinged, chromium plated case handles
- Edge mounting handle
- 3 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 castors with 2 locking brakes
- 4 built-in stacking trays in the cover

#### Package contents

- 1 x case, 1 x power cord, 1 x user manual

### Technical specifications:

Weight: 63,00 kg

### EUROLITE AKKU IP Pixel Tube 360° PRO CRMX

|                     |                                                                                                                  |
|---------------------|------------------------------------------------------------------------------------------------------------------|
| Power supply:       | 100-240 V AC, 50/60 Hz<br>13V DC 3000 mA                                                                         |
| IP classification:  | IP65                                                                                                             |
| Protection class:   | Protection class III                                                                                             |
| Power connection:   | Mains input via coaxial power connector (M)<br>power supply cord with AC unit (provided)<br>Battery/battery pack |
| Cable construction: | 2 x 0,75 mm² H03VVH2-F                                                                                           |
| Battery pack type:  | 1 x lithium ion 10,8 V, 9000 mAh, 97,2 Wh                                                                        |
| Battery pack:       | Battery operation up to 8,5h depending on<br>program used<br>Recharging time 4h                                  |
| Lamp type:          | LED lamp                                                                                                         |
| LED type:           | 144 x 0,5 W SMD 5050 5in1 PCL RGB/CW/WW<br>(homogenous color mix)                                                |
| Flash rate:         | 2 - 20 Hz                                                                                                        |
| DMX channels:       | 4; 5; 7; 14; 16; 20,1; 20,2; 22,1; 22,2; 24,1; 24,2;<br>120; 124                                                 |
| Cooling:            | Passive convection cooling                                                                                       |
| Control:            | Stand-alone; IR remote control; CRMX by<br>LumenRadio                                                            |
| Preprogrammed in:   | Light Captain; Colorchief                                                                                        |
| Projection:         | Flicker-free                                                                                                     |

|                              |                                                         |
|------------------------------|---------------------------------------------------------|
| PWM frequency:               | 12600 Hz                                                |
| Carrier frequency:           | 2,4 GHz                                                 |
| Modulation:                  | GFSK                                                    |
| DMX fail mode:               | Hold; blackout; static; full on                         |
| Beam angle:                  | 360°                                                    |
| Beam angle (1/2 peak):       | 360°                                                    |
| Beam angle (1/10 peak):      | 360°                                                    |
| Color rendering index (CRI): | 84 Ra                                                   |
| Housing color:               | Black matte                                             |
| Attachment system:           | 2x holding clip<br>M10 thread                           |
| Display type:                | Monochrome OLED display                                 |
| Display:                     | Charge status indicator , battery runtime calculation   |
| Material:                    | Plastic; aluminum                                       |
| Theft protection:            | KENSINGTON LOCK                                         |
| Dimensions:                  | Length: 109 cm<br>Width: 7,0 cm<br>Depth: 7,0 cm        |
| Weight:                      | 2,80 kg                                                 |
| Remote control               |                                                         |
| Battery:                     | 1 x button cell 3.0 V CR2032 lithium manganese built-in |

#### **ROADINGER Flightcase 8x AKKU IP Pixel Tube 360° PRO CRMX with charging function and wheels**

|                          |                                                                               |
|--------------------------|-------------------------------------------------------------------------------|
| Power supply:            | 100-240 V AC, 50/60 Hz                                                        |
| Power connection:        | Mains input via IP T-Con (M) power supply cord with safety plug (provided)    |
| Cable length:            | 1,2 m                                                                         |
| Fuse:                    | 5 x 20 mm, 5 A fuse replaceable                                               |
| Aluminum profile frames: | 35 mm                                                                         |
| Case handle:             | 4 pc/pcs                                                                      |
| Edge mounting handle:    | 1 pc/pcs                                                                      |
| Stop hinge:              | 3 pc/pcs                                                                      |
| Lock:                    | Butterfly lock: 2 pc/pcs                                                      |
| Transport aid:           | 4 x castors with 2 locking brakes<br>4 x built-in stacking trays in the cover |
| Color:                   | Black, laminated                                                              |
| Device compartment:      | 7 cm x 109 cm x 10 cm                                                         |
| Accessory compartment:   | 113 cm x 9 cm x 21 cm                                                         |
| Material thickness:      | 9 mm                                                                          |
| Dimensions:              | Width: 119 cm<br>Depth: 63 cm<br>Height: 45 cm                                |
| Weight:                  | 34,80 kg                                                                      |