

# EUROLITE Set 2x LED TMH-B120 Hypno Moving-Head Beam + Flightcase withwwheels45

GTIN: 4026397748345







List price: 1902.81 €

incl. 19% VAT.

# Features:

### **EUROLITE LED TMH-B120 Hypno Moving Head Beam**

LED moving head beam with hypno ring, color wheel, static gobo wheel, prism and focus

- 1 powerful LED 120 W COB (chip-on-board) cold white (CW)
- 30 powerful LEDs 0,2 W SMD 5050 3in1 TCL RGB (homogenous color mix)
- Positioning within 540° PAN, 240° TILT
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Color wheel; gobo wheel with static gobos; focus motor-driven; frost filter; prism 8-fold rotating
- Dimmer
- Beam effect
- Color wheel with 7 dichroic filters plus open<BR>half colors selectable, Rainbow effect with adjustable speed in both directions
- Gobo wheel with static gobos, 13 gobos und open<BR>shake effect
- 4 integrated show programs
- The device is cooled by cooling fan at the base; cooling fan at the Head
- Control via stand-alone; sound to light via microphone; DMX; QuickDMX via USB (optional);
   CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional);
   master/slave function
- Preprogrammed in Light Captain
- Flicker-free
- DMX fail mode (hold; zero values)
- With a beam angle of 2°
- With omega bracket
- Multicolor LCD display
- 2 Rugged carrying handles
- 4 x rubber feet

### Logistic

EAN / GTIN: 4026397748345

Weight: 32,00 kg Length: 0.00 m Width: 0.00 m Heigth: 0.00 m Bulky product

- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; stage; mobile djs / entertainer; rental
- Application possibility: Standing; suspended

#### Package contents

- 1 x moving light, 1 x power cord, 1 x omega bracket, 1 x safety eyelet, 1 x user manual

## ROADINGER Flightcase 2x TMH-B120 with wheels

Trunk case

- With 2 device compartment
- With 1 accessory compartment
- High-quality workmanship with plywood multi-layer glued 9 mm, black, laminated
- Interior with foam padding<BR>cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 x castors with 2 locking brakes

# **Technical specifications:**

Weight: 30,00 kg

### **EUROLITE LED TMH-B120 Hypno Moving Head Beam**

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	170 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Cable construction:	3 x 1,0 mm² H05VV-F
Cable length:	1,1 m
Power output:	P-Con (gray), mounting version
Fuse:	5 x 20 mm, T 2 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 120 W COB (chip-on-board) cold white (CW) 30 x 0,2 W SMD 5050 3in1 TCL RGB (homogenous color mix)
Max. TILT movement:	240° exact positioning (16 bit resolution) auto position correction (feedback)
Max. PAN movement:	540° exact positioning (16 bit resolution) auto position correction (feedback)
Flash rate:	1 - 20 Hz
Equipment:	Color wheel; gobo wheel with static gobos; focus motor-driven; frost filter; prism 8-fold rotating
Color generation:	Color wheel with 7 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed in both directions
Gobos:	Gobo wheel with static gobos, 13 gobos und open Shake effect

DMX input:  3-pin XLR (M) mounting version  DMX output:  3-pin XLR (F) mounting version  Cooling:  1 x cooling fan at the base 1 x cooling fan at the Head  Control:  Stand-alone; sound to light via microphone; DMX; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); CRMX by wireless solution via USB (optional); master/slave function  Preprogrammed in:  Light Captain  Projection:  Flicker-free  DMX fail mode:  Hold; zero values  Beam angle:  2°  Beam angle (1/2 peak):  Beam 2°  Ring 120°  Beam angle (1/10 peak):  Beam 2°  Ring 120°  Color temperature:  8500K  Housing color:  Black  Attachment system:  Omega bracket  Display type:  Multicolor LCD display  Status LED:  DMX, fault  USB port:  Type A  Carrying handle:  2 pc/pcs  Transport aid:  4 x rubber feet  Material:  Plastic  Dimensions:  Width: 26,0 cm Depth: 23,5 cm Height: 37,5 cm  Weight:  6,95 kg  Legal specifications  Special product:  Not designed for household room illumination  Intended use:  Show effect lighting	DMX channels:	21
Cooling:  1 x cooling fan at the base 1 x cooling fan at the Head  Control:  Stand-alone; sound to light via microphone; DMX; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional); master/slave function  Preprogrammed in:  Light Captain  Projection:  Flicker-free  DMX fail mode:  Hold; zero values  Beam angle:  2°  Beam angle (1/2 peak):  Beam angle (1/2 peak):  Beam angle (1/10 peak):  Beam angle (1/2	DMX input:	3-pin XLR (M) mounting version
1 x cooling fan at the Head  Control:  Stand-alone; sound to light via microphone; DMX; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional); master/slave function  Preprogrammed in:  Light Captain  Projection:  Flicker-free  DMX fail mode:  Hold; zero values  Beam angle:  2°  Beam angle (1/2 peak):  Beam 2°  Ring 120°  Beam angle (1/10 peak):  Beam 2°  Ring 120°  Color temperature:  8500K  Housing color:  Black  Attachment system:  Omega bracket  Display type:  Multicolor LCD display  Status LED:  DMX, fault  USB port:  Type A  Carrying handle:  2 pc/pcs  Transport aid:  4 x rubber feet  Material:  Plastic  Dimensions:  Width: 26,0 cm  Depth: 23,5 cm  Height: 37,5 cm  Weight:  6,95 kg  Legal specifications  Special product:  Not designed for household room illumination	DMX output:	3-pin XLR (F) mounting version
QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); w-DMX by wireless solution via USB (optional); master/slave function  Preprogrammed in:  Light Captain  Projection:  Flicker-free  DMX fail mode:  Beam angle:  2°  Beam angle (1/2 peak):  Beam 2°  Ring 120°  Beam angle (1/10 peak):  Beam 2°  Ring 120°  Color temperature:  8500K  Housing color:  Black  Attachment system:  Omega bracket  Display type:  Multicolor LCD display  Status LED:  DMX, fault  USB port:  Type A  Carrying handle:  2 pc/pcs  Transport aid:  4 x rubber feet  Material:  Plastic  Dimensions:  Width: 26,0 cm Depth: 23,5 cm Height: 37,5 cm  Weight:  6,95 kg  Legal specifications  Special product:  Not designed for household room illumination	Cooling:	-
Projection:  DMX fail mode:  Hold; zero values  Beam angle:  2°  Beam angle (1/2 peak):  Beam angle (1/10 peak):  Beam 2°  Ring 120°  Beam angle (1/10 peak):  Beam 2°  Ring 120°  Color temperature:  8500K  Housing color:  Black  Attachment system:  Omega bracket  Display type:  Multicolor LCD display  Status LED:  DMX, fault  USB port:  Type A  Carrying handle:  2 pc/pcs  Transport aid:  4 x rubber feet  Material:  Plastic  Dimensions:  Width: 26,0 cm  Depth: 23,5 cm  Height: 37,5 cm  Weight:  6,95 kg  Legal specifications  Special product:  Not designed for household room illumination	Control:	QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional); master/slave
DMX fail mode:  Beam angle:  Beam angle (1/2 peak):  Beam 2° Ring 120°  Beam angle (1/10 peak):  Beam 2° Ring 120°  Color temperature:  8500K  Housing color:  Black  Attachment system:  Omega bracket  Display type:  Multicolor LCD display  Status LED:  DMX, fault  USB port:  Type A  Carrying handle:  2 pc/pcs  Transport aid:  4 x rubber feet  Material:  Plastic  Dimensions:  Width: 26,0 cm Depth: 23,5 cm Height: 37,5 cm  Weight:  6,95 kg  Legal specifications  Special product:  Not designed for household room illumination	Preprogrammed in:	Light Captain
Beam angle:  Beam angle (1/2 peak):  Beam 2° Ring 120°  Beam 2° Ring 120°  Color temperature:  8500K  Housing color:  Black  Attachment system:  Omega bracket  Display type:  Multicolor LCD display  Status LED:  DMX, fault  USB port:  Type A  Carrying handle:  2 pc/pcs  Transport aid:  4 x rubber feet  Material:  Dimensions:  Width: 26,0 cm Depth: 23,5 cm Height: 37,5 cm  Weight:  6,95 kg  Legal specifications  Special product:  Not designed for household room illumination	Projection:	Flicker-free
Beam angle (1/2 peak):  Ring 120°  Beam angle (1/10 peak):  Beam 2° Ring 120°  Color temperature:  8500K  Housing color:  Black  Attachment system:  Omega bracket  Display type:  Multicolor LCD display  Status LED:  DMX, fault  USB port:  Type A  Carrying handle:  2 pc/pcs  Transport aid:  4 x rubber feet  Material:  Plastic  Dimensions:  Width: 26,0 cm Depth: 23,5 cm Height: 37,5 cm  Weight:  6,95 kg  Legal specifications  Special product:  Not designed for household room illumination	DMX fail mode:	Hold; zero values
Ring 120°  Beam angle (1/10 peak):  Beam 2° Ring 120°  Color temperature:  8500K  Housing color:  Black  Attachment system:  Omega bracket  Display type:  Multicolor LCD display  Status LED:  DMX, fault  USB port:  Type A  Carrying handle:  2 pc/pcs  Transport aid:  4 x rubber feet  Material:  Plastic  Dimensions:  Width: 26,0 cm Depth: 23,5 cm Height: 37,5 cm  Weight:  6,95 kg  Legal specifications  Special product:  Not designed for household room illumination	Beam angle:	2°
Ring 120°  Color temperature: 8500K  Housing color: Black  Attachment system: Omega bracket  Display type: Multicolor LCD display  Status LED: DMX, fault  USB port: Type A  Carrying handle: 2 pc/pcs  Transport aid: 4 x rubber feet  Material: Plastic  Dimensions: Width: 26,0 cm Depth: 23,5 cm Height: 37,5 cm  Weight: 6,95 kg  Legal specifications  Special product: Not designed for household room illumination	Beam angle (1/2 peak):	
Housing color:  Attachment system:  Omega bracket  Display type:  Multicolor LCD display  Status LED:  DMX, fault  USB port:  Type A  Carrying handle:  2 pc/pcs  Transport aid:  4 x rubber feet  Material:  Plastic  Dimensions:  Width: 26,0 cm Depth: 23,5 cm Height: 37,5 cm  Weight:  6,95 kg  Legal specifications  Special product:  Not designed for household room illumination	Beam angle (1/10 peak):	
Attachment system:  Display type:  Multicolor LCD display  Status LED:  DMX, fault  USB port:  Type A  Carrying handle:  2 pc/pcs  Transport aid:  4 x rubber feet  Material:  Plastic  Dimensions:  Width: 26,0 cm Depth: 23,5 cm Height: 37,5 cm  Weight:  6,95 kg  Legal specifications  Special product:  Not designed for household room illumination	Color temperature:	8500K
Display type:  Status LED:  DMX, fault  USB port:  Type A  Carrying handle:  2 pc/pcs  Transport aid:  4 x rubber feet  Material:  Plastic  Dimensions:  Width: 26,0 cm Depth: 23,5 cm Height: 37,5 cm  Weight:  6,95 kg  Legal specifications  Special product:  Not designed for household room illumination	Housing color:	Black
Status LED:  USB port:  Type A  Carrying handle:  2 pc/pcs  Transport aid:  4 x rubber feet  Material:  Plastic  Dimensions:  Width: 26,0 cm Depth: 23,5 cm Height: 37,5 cm  Weight:  6,95 kg  Legal specifications  Special product:  Not designed for household room illumination	Attachment system:	Omega bracket
USB port:  Carrying handle:  2 pc/pcs  Transport aid:  4 x rubber feet  Material:  Plastic  Dimensions:  Width: 26,0 cm Depth: 23,5 cm Height: 37,5 cm  Weight:  6,95 kg  Legal specifications  Special product:  Not designed for household room illumination	Display type:	Multicolor LCD display
Carrying handle:  2 pc/pcs  Transport aid:  4 x rubber feet  Material:  Plastic  Dimensions:  Width: 26,0 cm Depth: 23,5 cm Height: 37,5 cm  Weight:  6,95 kg  Legal specifications  Special product:  Not designed for household room illumination	Status LED:	DMX, fault
Transport aid:  4 x rubber feet  Material:  Plastic  Dimensions:  Width: 26,0 cm  Depth: 23,5 cm  Height: 37,5 cm  Weight:  6,95 kg  Legal specifications  Special product:  Not designed for household room illumination	USB port:	Туре А
Material:  Plastic  Width: 26,0 cm  Depth: 23,5 cm  Height: 37,5 cm  Weight:  6,95 kg  Legal specifications  Special product:  Not designed for household room illumination	Carrying handle:	2 pc/pcs
Dimensions:  Width: 26,0 cm Depth: 23,5 cm Height: 37,5 cm  Weight: 6,95 kg  Legal specifications  Special product:  Not designed for household room illumination	Transport aid:	4 x rubber feet
Depth: 23,5 cm Height: 37,5 cm  Weight: 6,95 kg  Legal specifications  Special product: Not designed for household room illumination	Material:	Plastic
Legal specifications  Special product:  Not designed for household room illumination	Dimensions:	Depth: 23,5 cm
Special product: Not designed for household room illumination	Weight:	6,95 kg
	Legal specifications	
Intended use: Show effect lighting	Special product:	Not designed for household room illumination
	Intended use:	Show effect lighting

# ROADINGER Flightcase 2x TMH-B120 with wheels

Maximum load:	50 kg
Aluminum profile frames:	30 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes
Material:	Plywood multi-layer glued, 9 mm, laminated
Color:	Black, laminated
Device compartment:	20,5 cm x 26 cm x 36 cm
Accessory compartment:	8 cm x 26 cm x 19 cm
·	

Dimensions: Width: 57 cm
Depth: 31,5 cm

Height: 59 cm

Weight: 14,00 kg