



List price: 2278.85 €

incl. 19% VAT.

Features:

EUROLITE AKKU IP UP-4 QCL Spot QuickDMX MK2

Weather-proof (IP65) battery powered LED uplight with 10W 4in1 LEDs and QuickDMX

- Integrated QuickDMX transceiver for wireless DMX control
- Cordless, flexible and versatile
- Battery operation up to 5.5h depending on program used
- Integrated automatic charging of the battery and status indicator
- 4 LEDs 10 W SMD 5050 4in1 QCL RGBW (homogenous color mix)
- Frost filter
- Dimmer electronic; Dimmer speed (step response) adjustable; color blend stepless; color fade adjustable speed; color change adjustable speed; colors preset; white balance adjustable; program selection manual; pulse-width modulation; Energy-saving mode; Emergency lighting function in case of power failure
- Wash effect; strobe effect
- 36 integrated show programs
- Direct color selection for 15 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; IR remote control; DMX; QuickDMX; RDM; master/slave function; wireless Master/slave function
- Flicker-free
- DMX fail mode (blackout; hold; static; full on)
- With a beam angle of 8°
- With mounting bracket; with bracket for floor use; with omega bracket
- OLED display
- Charge status indicator
- Display of the remaining battery life for the current setting
- Built with SEETRONIC connector

Logistic

EAN / GTIN: 4026397625813

Weight: 40,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

Bulky product

- Suitable for outdoor use IP65
- With pressure compensation membrane
- With a KENSINGTON LOCK theft protection
- For application areas such as: Architecture; decoration; wedding/gala/events; mobile djs / entertainer; restaurants, bars and hotels; rental; advertisement/Shop window
- Silent operation
- Application possibility: Standing; suspended
- 3 buttons on the remote control for saving your own settings

ROADINGER Flightcase 4x AKKU IP UP-4 QuickDMX with charging function

Trunk case with castors

- With accessory compartment
- With 4 device compartments
- High-quality workmanship with plywood multi-layer glued 9 mm, black, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks with shut-off function
- 4 x castors with 2 locking brakes
- 4 x built-in stacking trays in the cover

Technical specifications:

Weight: 33.53 kg

EUROLITE AKKU IP UP-4 QCL Spot QuickDMX MK2

Power supply:	100-240 V AC, 50/60 Hz
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug
Cable construction:	3 x 1.5 mm ² H07RN-F
Battery pack type:	1 x lithium ion 14.8 V, 6600 mAh, 97.68 Wh
Battery pack:	Battery operation up to 5.5h depending on program used Recharging time 3h
Lamp type:	LED lamp
LED type:	4 x 10 W SMD 5050 4in1 QCL RGBW (homogenous color mix)
Equipment:	Frost filter
DMX channels:	3; 4; 6; 8; 11
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	Stand-alone; IR remote control; DMX; QuickDMX; RDM; master/slave function; wireless Master/slave function
Projection:	Flicker-free

PWM frequency:	3000 Hz
Carrier frequency:	2.4 GHz
DMX fail mode:	Blackout; hold; static; full on
Beam angle:	8°
Beam angle (1/2 peak):	8°
Beam angle (1/10 peak):	17°
Housing color:	Black
Attachment system:	Mounting bracket Bracket for floor use Omega bracket
Display type:	OLED display
Display:	Charge status indicator , battery runtime calculation
Diameter mounting holes:	1 x Ø10mm
Use of brands:	Built with SEETRONIC connector
Material:	Aluminum
Theft protection:	KENSINGTON LOCK
Dimensions:	Width: 17.9 cm Depth: 15.0 cm Height: 19.8 cm
Weight:	4.57 kg
Noise classification:	Class 0 (no noise at all)
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x AKKU IP UP-4 QuickDMX with charging function

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	Max. 1150 W
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug (provided)
Device fuse:	5 x 20 mm, F 5 A fuse replaceable
Aluminum profile frames:	25 mm
Case handle:	4 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs with shut-off function
Transport aid:	4 x castors with 2 locking brakes 4 x built-in stacking trays in the cover
Material:	Plywood multi-layer glued, 9 mm
Color:	Black, laminated
Device compartment:	18 cm x 15.5 cm x 14 cm
Accessory compartment:	7 cm x 43 cm x 14 cm
Inside dimensions:	56 cm x 43 cm x 20 cm
Dimensions:	Width: 60 cm

Depth: 47.5 cm

Height: 41 cm

Weight:	15.25 kg
Cable construction:	3 x 1.5 mm ² H07RN-F
Cable length:	1.2 m detachable

Scope of delivery:

4 x EUROLITE AKKU IP UP-4 QCL Spot QuickDMX MK2

- 1 x spotlight
- 1 x user manual
- 1 x power cord
- 1 x frost filter
- 1 x remote control
- 1 x battery
- 2 x knurled screw
- 1 x mounting bracket
- 2 x screw
- 4 x washer
- 1 x omega bracket

1 x ROADINGER Flightcase 4x AKKU IP UP-4 QuickDMX with charging function

- 1 x case
- 1 x power cord
- 4 x castors
- 16 x screw
- 1 x key
- 1 x user manual