

NEUTRIK RCA plug Pro NF2CB 2x
PRO RCA plug

Art. No.: 30204050

GTIN: 7613187001109



The article is no longer in our assortment.

Features:

- Professional RCA plug with gold plated contacts and spring loaded ground contact
- Direct electrical connection from ground contact to the signaling path
- Easy assembly and soldering (large soldering area, rapid-flow plating)

Logistic

EAN / GTIN: 7613187001109

Weight: 0,05 kg

Length: 0.14 m

Width: 0.10 m

Height: 0.01 m

Technical specifications:

Rated current:	16 A
Rated voltage:	50 V ac
Insulation resistance:	>100 Gohms
Dielectric strength:	1500 V DC
Capacitance (pin to shell):	7 pF
Cable anchoring:	Neutrik chuck principle
Cable OD range:	3.0-5.5 mm (blue chuck) and 5.5-7.3 mm (black chuck)
Max. wire size:	2.5 mm ² / 14 AWG
Solderability:	complies with IEC 68-2-20
Shell:	Brass CuZn39Pb3 black coated
Contact pin:	Brass CuZn39Pb3 0.5 mm Au plated
Ground contact:	Brass CuZn39Pb3 0.5 µm Au plated over 5 µm Ni

Chuck:	Polyacetal POM
Insulator:	PBTP
Temperature range:	-30°C to +80°C