

SOMMER CABLE SC-CICADA SO-D14 50m
High-quality cable

Art. No.: 3030744R
GTIN: 4026397424348



The article is no longer in our assortment.

Features:

- Highly flexible due to the fine copper strand construction
- Easy to work with due to the additional filler strand (0.22 mm²)
- Outstanding shielding due to dense spiral shielding, 95 % optically opaque
- Longevity and resistant to notching due to the tough PUR-jacket

Logistic

EAN / GTIN: 4026397424348
Weight: 0,68 kg
Length: 0.27 m
Width: 0.23 m
Heigth: 0.03 m

Technical specifications:

| | |
|-----------------------------------|--|
| Color: | Black |
| Construction: | (2LI2Y0,14 mm²) DY |
| Jacket, diameter: | PUR Master Blend 2,6 mm |
| AWG: | 26 |
| No. of inner conductors: | 2 x 0,14 mm² |
| Copper strand per conductor: | 18 x 0,10 mm |
| Cond. insulationCond. insulation: | PE 0,90 mm |
| Shielding: | copper spiral shielding + filler strand, tin-plated (0.22 mm²) |
| Shielding factor: | 95 % |
| Temperature range: | min. -30° C |
| Temperature range: | max. 70° C |

| | |
|-------------------------------|-----------|
| Fire load per m: | 0,08 kWh |
| Weight per 1 m: | 13 g |
| Packaging: | 50 m roll |
| ELECTRICAL DATA: | |
| Capac. cond./cond. per 1 m: | 65 pF |
| Capac. cond./shield. per 1 m: | 120 pF |
| Cond. resistance per 1 km: | <148 ohms |
| Shield. resistance per 1 km: | 30 ohms |
| Insulation resist. per 1 km: | >1 Gohms |