

SOMMER CABLE DMX cable XLR 5pin 1m bk Hicon

High-quality data cable

Art. No.: 3030746H GTIN: 4049371168595



The article is no longer in our assortment.

Description:

DMX cable by premium manufacturer Sommer Cable

These premade cables are the perfect choice for the transmission of the 110 ohms AES/EBU DMX512 data format.

Important note: the use of a standard microphone cable is not recommended due to data and information losses (caused by the skin effect). In the lighting domain data losses cause a total jam with signal transmissions or the control of scanner systems.

The very affordable price of this cable should make it easy to switch from a standard microphone cable to a proper AES/EBU cable. Our AES/EBU cable guarantees the error-free data transfer even over longer distances of up to 100 metres. We use the BINARY 434 AES/EBU MKII AES/EBU cable with 100 % shielding and the HICON XLR connectors.

Features:

- AES/EBU- and DMX-conformant, highly flexible
- Very good shielding through the use of copper spiral shielding and a fleece vaporized with aluminum
- Extremely robust with an especially strong jacket
- Only a little more expensive than a standard microphone cable
- For networking of scanners, lighting units, digital mixing boards, etc.
- For indoor and outdoor installation
- For connection of digital audio amplifiers, DAT-recorders, etc.
- HICON

Logistic

EAN / GTIN: 4049371168595

Weight: 0,17 kg Length: 0.20 m Width: 0.24 m Heigth: 0.04 m

Technical specifications:

Pin configuration:	Pin 1 (GND) / Pin 2 (+) / Pin 3 (-) / Pin 4 (Data) / Pin 5 (Data)
Cable length:	1 m
Plug A:	1 x 5-pin XLR (M)
Plug B:	1 x 5-pin XLR (F)
Use of brands:	HICON
Color:	Black
Weight:	140 g