eurolite®

EUROLITE MIK-250S Outdoor spot, E40, silv

Compact 250 W outdoor floodlight











The article is no longer in our assortment.

Features:

- Stylish static spot

- With asymmetrical or symmetrical reflector
- For architectural lighting or large stage backgrounds
- Aluminum die-cast housing
- Jet-proof construction for outdoor use
- Ready for connection with silicone cable and safety-plug
- For bright 250 W discharge lamp
- Available in black, silver or white

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	275,00 W
IP classification:	IP65
Dimensions:	Width: 24,5 cm
	Depth: 47,5 cm
	Height: 28 cm
Protection grade:	IP65
Dimensions (L x W x H):	475 x 370 x 280 mm
Weight:	10 kg

Logistic

EAN / GTIN: 4026397247510 Weight: 9,20 kg Length: 0.47 m Width: 0.33 m Heigth: 0.26 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.