# eurolite®

## EUROLITE GKF-250S Outdoor Spot 250W E40 bk

Static spot as outdoor floodlight (IP65)

## Art. No.: 40000353

GTIN: 4026397365146



# The article is no longer in our assortment.

#### Features:

- For architectural lighting or large stage backgrounds
- Symmetrical, i.e. the same radiation angle upwards and downwards
- Aluminum die-cast housing
- Jet-proof construction for outdoor use
- Ready for connection via silicone cable with safety-plug
- For bright HQI discharge lamps
- Housing color: black
- Available in 150 W, 250 W or 400 W version
- The device is cooled by passive convection cooling
- Suitable for outdoor use IP65

### **Technical specifications:**

Power supply:	230 V AC, 50 Hz
Power consumption:	300 W
IP classification:	IP65
Lamp type:	Discharge lamp
Cooling:	Passive convection cooling
Housing color:	Black
Dimensions:	Width: 22 cm
	Depth: 43 cm



EAN / GTIN: 4026397365146 Weight: 10,35 kg Length: 0.48 m Width: 0.48 m Heigth: 0.21 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

	Height: 47 cm
Weight:	8,50 kg
Protection grade:	IP65
Fitting lamp:	OMNILUX OQI-T 250W E40
Dimensions (L x W x H):	470 x 220 x 430 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting