

EUROLITE LED IP PFE-40 CW/WW 15-30°

Weather-proof spotlight (IP65), 40 W COB LED, variable color temperature, CRI >90, RDM

Art. No.: 40001705

GTIN: 4026397718669



List price: 831.81 €

incl. 19% VAT.

Features:

- 4 shutter blades
- 1 powerful LED 40 W COB (chip-on-board) 2in1 BCL CW/WW (homogenous color mix)
- Zoom manual; focus manual
- Dimmer electronic; Dimmer speed (step response) adjustable; pulse-width modulation variable
- Strobe effect
- Control via stand-alone; master/slave function; DMX; RDM
- Preprogrammed in Light´J; Light Captain
- With a beam angle of 15° - 30°
- Variable color temperature 2700 K - 6000 K
- Very high color rendering index (CRI)
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- Very quiet working noise
- For application areas such as: Trade fair and shop fitting; installation; stage; theater
- Application possibility: Suspended; on stand

Package contents

- 1 x device, 1 x gobo holder, 1 x filter frame, 1 x user manual, 1 x power cord, 1 x adapter cable, 1 x safety bond

Logistic

EAN / GTIN: 4026397718669

Weight: 4,50 kg

Length: 0.44 m

Width: 0.21 m

Height: 0.23 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 30 W

IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug (provided)
Lamp type:	LED lamp
LED type:	1 x 40 W COB (chip-on-board) 2in1 BCL CW/WW (homogenous color mix)
Equipment:	Zoom manual; focus manual
DMX channels:	1; 2; 3; 6
DMX input:	1 x 3-pin XLR (M) mounting version IP
Control:	Stand-alone; master/slave function; DMX; RDM
Preprogrammed in:	Light'J; Light Captain
Beam angle:	15° - 30°
Beam angle (1/2 peak):	15 - 30°
Beam angle (1/10 peak):	15 - 30°
Color temperature:	2700K - 6000K adjustable
Color rendering index (CRI):	92 Ra
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Length: 34,5 cm Width: 15,5 cm Height: 28,5 cm
Weight:	3,95 kg
Noise classification:	Class 1 (very slight noise, suitable for noise- sensitive environments)
Gobo holder	
Gobos:	Outside diameter 37,5mm Image diameter 28mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting