

EUROLITE LED PFE-60 RGBW Profile Spot 20-50°

Profile spotlight, 80 W 4in1 LED (RGBW), manual Zoom, shutter blades

Art. No.: 40001732

GTIN: 4026397715491



List price: 546.21 €

incl. 19% VAT.

Features:

- 1 LED 80 W COB (chip-on-board) 4in1 RGBW (homogenous color mix)
- Zoom manual; focus manual
- Variable color temperature 1800 K - 10000 K
- Good color rendering index (CRI)
- Very quiet working noise
- Flicker-free
- Control via stand-alone; DMX; RDM; master/slave function
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; pulse-width modulation variable
- Strobe effect
- With mounting bracket
- Multicolor OLED display
- The device is cooled by temperature-controlled fan
- For application areas such as: Stage; clubs/dancing school; wedding/gala/events; Trade fair and shop fitting; restaurants, bars and hotels; theater; rental
- Application possibility: Suspended; on stand

Logistic

EAN / GTIN: 4026397715491

Weight: 3,71 kg

Length: 0.42 m

Width: 0.20 m

Height: 0.23 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	60 W
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug

Cable length:	Approx. 1 m
Fuse:	5 x 20 mm, T 1 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 80 W COB (chip-on-board) 4in1 RGBW (homogenous color mix)
Flash rate:	1 - 19 Hz
Equipment:	Zoom manual; focus manual
DMX channels:	5; 6; 9
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	Stand-alone; DMX; RDM; master/slave function
Fixtures available for:	Light Captain
Projection:	Flicker-free
Beam angle (1/2 peak):	20 - 50°
Beam angle (1/10 peak):	20 - 50°
Color temperature:	1800K - 10000K adjustable
Color rendering index (CRI):	82 Ra
Lamp life:	50000 h
Luminous flux:	5000 lm
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	Multicolor OLED display
Dimensions:	Length: 35.0 cm Width: 16.0 cm Height: 25.5 cm
Weight:	3.21 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Energy efficiency class (A - G):	F
EPREL-Nr:	1597530
Diameter mounting holes:	1 x Ø12mm
Material:	Metal, 3 mm
Gobos:	Outside diameter 37mm Image diameter 25mm
Material:	Aluminum, 0.5 mm; plastic
Dimensions:	Diameter: Ø 3 cm

Scope of delivery:

1 x spotlight
1 x gobo holder
1 x user manual