

EUROLITE LED Mini PFE-12 CW

Fanless spotlight with 12 W COB LED, adjustable light beam shape, color rendering index (CRI) >90

Art. No.: 40001762

GTIN: 4026397742114



List price: 71.28 €

incl. 19% VAT.

Features:

- 1 powerful LED COB (chip-on-board)
- Focus manual
- 4 shutter blades
- Spot effect
- The device is cooled by passive convection cooling
- With a beam angle of 28°
- Very high color rendering index (CRI)
- For application areas such as: Trade fair and shop fitting; installation; restaurants, bars and hotels; video and photography
- Very quiet working noise
- Easy installation
- Application possibility: Standing; suspended
- With mounting bracket
- Various versions available
- **knurled screw**
- M4 thread
- **Package contents**
- 1 x device, 1 x key, 1 x user manual

Logistic

EAN / GTIN: 4026397742114

Weight: 0,67 kg

Length: 0.24 m

Width: 0.20 m

Height: 0.14 m

Technical specifications:

Power supply: 230 V AC, 50 Hz

Power consumption: 12 W

IP classification: IP20

Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Cable construction:	3 x 0,75 mm² H05VV-F
LED type:	1 x COB (chip-on-board)
Equipment:	Focus manual
Cooling:	Passive convection cooling
Setup:	Easy installation
Beam angle:	28°
Beam angle (1/2 peak):	28°
Color temperature:	5800K
Color rendering index (CRI):	91 Ra
Illuminance in Lux (lx):	1m: 2103 lx, 3m: 231 lx, 6m: 91 lx
Luminous flux:	1080 lm
Housing color:	Black matte
Attachment system:	Mounting bracket
Material:	Aluminum casting
Dimensions:	Length: 19 cm Width: 8,5 cm Height: 12,5 cm
Weight:	0,50 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Energy efficiency class (A - G):	F
Mounting bracket	
Diameter mounting holes:	1 x Ø10mm
Material:	Metal, 1 mm
Knurled screw	
Thread:	M4 thread x 16 mm