EUROLITE LED PFE-20 WW Profile Spot bk

Handy stage spotlight with 20 W COB LED, CRI >95

Art. No.: 40001766

GTIN: 4026397693072

List price: 213.01 €

incl. 19% VAT.

Features:

- 1 powerful LED 20 W COB (chip-on-board) warm white (WW)
- With a beam angle of 19°
- 4 shutter blades
- The device is cooled by passive convection cooling
- Dimmer electronic
- Flicker-free
- Very high color rendering index (CRI)
- With Mounting bracket
- For application areas such as: Trade fair and shop fitting; Installation; restaurants, bars and hotels; video and photography
- Silent operation
- Application possibility: Suspended; on stand

  Screw
- M5 thread

  Package contents
- 1 x spotlight, 1 x gobo holder, 1 x power cord, 1 x filter frame, 2 x screw, 2 x washer, 1 x user manual

Logistic

EAN / GTIN: 4026397693072

Weight: 1,40 kg

Length: 0.25 m

Width: 0.13 m

Heigth: 0.15 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	20 W
IP classification:	IP20

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Protection class:	Protection class I
Power connection:	Mains input via 3-pin screw plug connector (M) mounting version power supply cord with safety plug (provided)
Fuse:	5 x 20 mm, T 0,5 A Fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 20 W COB (chip-on-board) warm white (WW)
Cooling:	Passive convection cooling
Projection:	Flicker-free
Beam angle:	19°
Beam angle (1/2 peak):	19°
Color temperature:	3000K
Color rendering index (CRI):	96 Ra
Illuminance in Lux (lx):	Warm white (WW) 1m: 3849 lx, 3m: 460 lx, 6m: 116 lx
Housing color:	Black
Attachment system:	Mounting bracket
Material:	Aluminum casting; metal; plastic
Dimensions:	Length: 22,2 cm Width: 15,8 cm Height: 20,3 cm
Weight:	1,23 kg
Noise classification:	Class 0 (no noise at all)
Gobo holder	
Gobos:	Outside diameter 42mm Image diameter 18mm
Material:	Aluminum, 0,3 mm
Dimensions:	Width: 4,4 cm Height: 10,1 cm Diameter: Ø 3,4 cm
Power cord	
Cable construction:	3 x 0,75 mm² H05VV-F
Cable length:	Approx. 1,4 m
Filter frame	
Material:	Aluminum, 0,3 mm
Dimensions:	Width: 6,9 cm Height: 6,9 cm Diameter: Ø 5,6 cm
Mounting bracket	
Diameter mounting holes:	1 x Ø11mm; 2 x Ø7mm
Material:	Aluminum casting, 2 mm
Screw	
Thread:	M5 thread x 11 mm
Washer	
Material:	Plastic
Color:	Pink
Dimensions:	Height: 1 mm

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

	Diameter: Ø 1,2 cm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.