

## EUROLITE LED PPC-20 WW Spot

Fanless spotlight with 20 W COB LED, adjustable beam angle, color rendering index (CRI) >95

Art. No.: 40001775

GTIN: 4026397701364



**List price: 165.41 €**

incl. 19% VAT.

### Features:

- Four beam angles adjustable via lens settings within the housing
- With plano-convex lens
- 1 powerful LED 20 W COB (chip-on-board) warm white (WW)
- The device is cooled by passive convection cooling
- Control via rotary dial for brightness
- Flicker-free
- With a beam angle of 10°
- Very high color rendering index (CRI)
- For application areas such as: Trade fair and shop fitting; installation; restaurants, bars and hotels; video and photography
- Silent operation
- Application possibility: Suspended; on stand

#### Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x mounting bracket, 1 x screw

### Logistic

EAN / GTIN: 4026397701364

Weight: 1,32 kg

Length: 0.25 m

Width: 0.14 m

Height: 0.15 m

### Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 15 W

IP classification: IP20

Protection class: Protection class I

Power connection:	Mains input via 3-pin screw plug connector (M) mounting version power supply cord with safety plug (provided)
Device fuse:	5 x 20 mm, T 0,5 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 20 W COB (chip-on-board) warm white (WW)
Cooling:	Passive convection cooling
Control:	Rotary dial for brightness
Projection:	Flicker-free
Beam angle:	10°
Beam angle (1/2 peak):	10° 15° 18° 22°
Beam angle (1/10 peak):	19° 27° 30° 34°
Color temperature:	3000K
Color rendering index (CRI):	97 Ra
Illuminance in Lux (lx):	Narrow warm white (WW) 1m: 6073 lx, 3m: 742 lx, 6m: 194 lx  Wide warm white (WW) 1m: 2718 lx, 3m: 350 lx, 6m: 92 lx
Housing color:	Black
Dimensions:	Length: 19,5 cm Width: 11,5 cm Height: 16,5 cm
Weight:	1,12 kg
Noise classification:	Class 0 (no noise at all)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting