eurolite®

EUROLITE LED PFE-50 3000K Profile Spot

Handy stage spotlight with 50 W COB LED in modular construction system, CRI >80

Art. No.: 40001800

GTIN: 4026397579284











List price: 355.81 €

incl. 19% VAT.

Features:

- Modular construction kit that can be customized to individual preferences
- 4 shutter blades
- Dimmer and strobe, master/slave functions adjustable via optional DMX interface
- 1 powerful LED 50 W COB (chip-on-board) warm white (WW)
- The device is cooled by cooling fan
- Control via on/off switch on device; master/slave function
- Preprogrammed in LED PC-Control 512; Light Captain; Light'J
- Flicker-free
- With a beam angle of 19°
- Very high color rendering index (CRI)
- With mounting bracket
- Very quiet working noise
- Dimmable
- For application areas such as: Trade fair and shop fitting; installation; theater; rental
- Application possibility: Suspended; on stand
- Package contents
- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x filter frame, 1 x gobo holder, 1 x terminating plug (power)

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	55 W
IP classification:	IP20

Logistic

EAN / GTIN: 4026397579284 Weight: 2,45 kg Length: 0.38 m Width: 0.20 m Heigth: 0.20 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Power connection:	Mains input via 3-pin screw plug connector (M) IP power supply cord with safety plug (provided)
Power output:	1 x 3-pin screw plug connector (F) IP
Lamp type:	LED lamp
Lamp specification:	Dimmable
LED type:	1 x 50 W COB (chip-on-board) warm white (WW)
Cooling:	Cooling fan
Control:	On/off switch on device; master/slave function
Preprogrammed in:	LED PC-Control 512; Light Captain; Light J
Projection:	Flicker-free
Beam angle:	19°
Beam angle (1/2 peak):	19° (optional) 26° (optional) 36° (optional) 50° (optional)
Color temperature:	3000K
Color temperature: Color rendering index (CRI):	3000K 91 Ra
· · · · · · · · · · · · · · · · · · ·	
Color rendering index (CRI):	91 Ra Warm white (WW) 1m: 0 lx, 3m: 1669 lx, 6m: 432
Color rendering index (CRI): Illuminance in Lux (Ix):	91 Ra Warm white (WW) 1m: 0 lx, 3m: 1669 lx, 6m: 432 lx
Color rendering index (CRI): Illuminance in Lux (Ix): Housing color:	91 Ra Warm white (WW) 1m: 0 lx, 3m: 1669 lx, 6m: 432 lx Black
Color rendering index (CRI): Illuminance in Lux (lx): Housing color: Attachment system:	91 Ra Warm white (WW) 1m: 0 lx, 3m: 1669 lx, 6m: 432 lx Black Mounting bracket Length: 30,5 cm Width: 13,4 cm
Color rendering index (CRI): Illuminance in Lux (lx): Housing color: Attachment system: Dimensions:	91 Ra Warm white (WW) 1m: 0 lx, 3m: 1669 lx, 6m: 432 lx Black Mounting bracket Length: 30,5 cm Width: 13,4 cm Height: 23,8 cm
Color rendering index (CRI): Illuminance in Lux (lx): Housing color: Attachment system: Dimensions: Weight:	91 Ra Warm white (WW) 1m: 0 lx, 3m: 1669 lx, 6m: 432 lx Black Mounting bracket Length: 30,5 cm Width: 13,4 cm Height: 23,8 cm 1,97 kg Class 1 (very slight noise, suitable for noise-
Color rendering index (CRI): Illuminance in Lux (lx): Housing color: Attachment system: Dimensions: Weight: Noise classification:	91 Ra Warm white (WW) 1m: 0 lx, 3m: 1669 lx, 6m: 432 lx Black Mounting bracket Length: 30,5 cm Width: 13,4 cm Height: 23,8 cm 1,97 kg Class 1 (very slight noise, suitable for noise-