

EUROLITE LED PLL-704 6000K Panel

DMX-controlled surface light with 704 cold white LEDs, QuickDMX port and barn doors

Art. No.: 40001835

GTIN: 4026397700244



List price: 593.81 €

incl. 19% VAT.

Features:

- 704 powerful LEDs SMD 2835 cold white (CW)
 - Energy-saving, durable and environmentally friendly
 - 4 barn doors to avoid blinding the audience and for protection during transport
 - Pulse-width modulation variable
 - The device is cooled by passive convection cooling
 - Control via stand-alone; DMX; quick select potentiometer for brightness and flash rate; master/slave function; sound to light via microphone; W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); QuickDMX via USB (optional)
 - Flicker-free
 - With a beam angle of 120°
 - Good color rendering index (CRI)
 - With mounting bracket
 - LCD display
 - Slim, rugged metal housing
 - For application areas such as: Video and photography; stage; Trade fair and shop fitting; mobile use
 - Preprogrammed in Light Captain; Light´J
 - Mains input and output for power linking up to 8 units
 - Rugged carrying handle
 - Silent operation
 - Application possibility: Suspended; on stand
- Package contents**
- 1 x spotlight, 1 x power cord, 1 x user manual

Logistic

EAN / GTIN: 4026397700244

Weight: 8,50 kg

Length: 0.57 m

Width: 0.18 m

Height: 0.40 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	140 W
IP classification:	IP20
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Fuse:	T 3 A fuse replaceable
Lamp type:	LED lamp
LED type:	704 x SMD 2835 cold white (CW)
Flash rate:	0 - 20 Hz
DMX channels:	1; 2; 3
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; quick select potentiometer for brightness and flash rate; master/slave function; sound to light via microphone; W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); QuickDMX via USB (optional)
Preprogrammed in:	Light Captain; Light´J
Projection:	Flicker-free
Beam angle:	120°
Beam angle (1/2 peak):	120°
Color temperature:	6000K
Color rendering index (CRI):	80 Ra
Illuminance in Lux (lx):	Cold white (CW) 1m: 4111 lx, 3m: 598 lx, 6m: 182 lx
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	LCD display
Carrying handle:	1 pc/pcs
Dimensions:	Width: 56,5 cm Depth: 25,5 cm Height: 42,2 cm
Weight:	7,70 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting