

EUROLITE LED PLL-360 3200K Panel

Surface light with 360 warm white LEDs and DMX

Art. No.: 40001890

GTIN: 4026397616804



List price: 510.51 €

incl. 19% VAT.

Features:

- Energy-saving, durable and environmentally friendly
- Milky diffuser provides a soft, homogeneous light
- 4 barn doors to avoid blinding the audience and for protection during transport
- Electronic dimmer (0-100%)
- 4 dimmer speeds selectable
- Quick brightness setting via rotary dial
- Slim, rugged metal housing
- Mains input and output for power linking up to 8 units
- 360 powerful LEDs 0,5 W SMD 2835 warm white (WW)
- Can be operated in 3 CH mode
- The device is cooled by passive convection
- Controlling by DMX; Master/slave function
- Preprogrammed in Light 'J; Light Captain
- Flicker-free
- Effect: Strobe effect
- With a beam angle of 120°
- Very high color rendering index (CRI)
- With Mounting bracket
- LCD display for easy controlling
- 1 hinged, chromium plated case handle
- Available as versions
- For application areas such as: Video- and Photographic; Stage

Package contents

- 1 x Spotlight, 1 x User manual, 1 x Power cord

Logistic

EAN / GTIN: 4026397616804

Weight: 6,95 kg

Length: 0.63 m

Width: 0.15 m

Height: 0.37 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	130 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	IEC connector (F) mounting version
Lamp type:	LED lamp
Lamp specification:	Dimmable
LED:	360 x 0,5 W SMD 2835 warm white (WW)
Color temperature:	3180K
DMX channels:	3
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection
Control:	DMX; Light J; Light Captain; Master/slave function
Beam angle:	120°
Beam angle (1/2 peak):	120°
Color rendering index (CRI):	94 Ra
Illuminance in Lux (lx):	Warm white (WW) 3m: 403 lx, 6m: 118 lx
Luminous flux:	9367 lm
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	LCD display
Case handles:	1 pc/pcs
Dimensions:	Width: 57 cm Depth: 12 cm Height: 31 cm
Weight:	6,10 kg
Noise classification:	Class 0 (no noise at all)
Energy efficiency class (A - G):	F