

EUROLITE LED PLL-384 CW/WW Panel

DMX-controlled surface light with 384 dual white LEDs, QuickDMX port, diffuser and barn doors

Art. No.: 40001892

GTIN: 4026397698541



List price: 355.81 €

incl. 19% VAT.

Features:

- Ideal for photography, film, stage and trade fair lighting
- Variable color temperature 2700-5700 K
- 69 preset color temperatures
- Quick color temperature and brightness setting via rotary dials
- Energy-saving, durable and environmentally friendly
- Milky diffuser provides a homogeneous and soft continuous light
- 4 barn doors to avoid blinding the audience and for protection during transport
- Electronic dimmer (0-100%)
- Strobe effect 1-20 Hz
- Supports QuickDMX - the wireless DMX system from Eurolite
- Mains input and output for power linking up to 8 units
- 192 powerful LEDs 0,5 W SMD 5730 cold white (CW)
- 192 powerful LEDs 0,5 W SMD 5730 warm white (WW)
- Can be operated in 2-1; 2-2; 3-1; 3-2; 4 CH mode
- The device is cooled by temperature-controlled fan
- Controlling by DMX; Master/slave function; stand-alone; CRMX by LumenRadio via USB (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); Quick select potentiometer for brightness and color temperature
- Flicker-free projection
- With a beam angle of 50°
- Very high color rendering index (CRI)
- With Mounting bracket
- LCD display for easy controlling
- With 4 rubber feet

Logistic

EAN / GTIN: 4026397698541

Weight: 3,90 kg

Length: 0.37 m

Width: 0.19 m

Height: 0.24 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	100 W
IP classification:	IP20
Protection class:	Class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Lamp type:	LED lamp
LED:	192 x 0,5 W SMD 5730 cold white (CW) 192 x 0,5 W SMD 5730 warm white (WW)
Color temperature:	2700K - 5700K adjustable
Flash rate:	1 - 20 Hz
DMX channels:	2-1; 2-2; 3-1; 3-2; 4
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	DMX; Master/slave function; stand-alone; CRMX by LumenRadio via USB (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); Quick select potentiometer for brightness and color temperature
Beam angle:	50°
Beam angle (1/2 peak):	50°
Beam angle (1/10 peak):	100°
Color rendering index (CRI) more than:	90 Ra
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	LCD display
Transport aid:	4 x rubber feet
Dimensions:	Length: 34,7 cm Width: 13,8 cm Height: 21,1 cm
Weight:	3,52 kg
Noise classification:	Class 0 (no noise at all)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting