

EUROLITE LED PLL-480 QCL Panel

DMX-controlled surface light with 480 4in1 RGBW LEDs

Art. No.: 40001898

GTIN: 4026397688610



List price: 808.01 €

incl. 19% VAT.

Features:

- Energy-saving, durable and environmentally friendly
- Milky diffuser provides a soft, homogeneous light
- 4 barn doors to avoid blinding the audience and for protection during transport
- Stepless color blend, color change, color fade, dimmer and strobe effect
- Variable PWM frequency (pulse-width modulation)
- Slim, rugged metal housing
- Stand or truss installation
- Mains input and output for power linking up to 8 units
- 480 powerful LEDs SMD 5050 4in1 QCL RGBW (homogenous color mix)
- Can be operated in 6; 4 CH mode
- The device is cooled by passive convection
- Controlling by DMX; stand-alone; Master/slave function
- Preprogrammed in Light 'J; Light Captain
- Flicker-free
- With a beam angle of 120°
- With Mounting bracket
- LCD display for easy controlling
- 1 hinged, chromium plated case handle
- For application areas such as: Video- and Photographic; Stage

Package contents

- 1 x Spotlight, 1 x User manual, 1 x Power cord, 1 x Plug (male)

Logistic

EAN / GTIN: 4026397688610

Weight: 13,50 kg

Length: 0.71 m

Width: 0.20 m

Height: 0.40 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	204 W
IP classification:	IP20
Protection class:	Class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Lamp type:	LED lamp
LED:	480 x SMD 5050 4in1 QCL RGBW (homogenous color mix)
DMX channels:	6; 4
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection
Control:	DMX; Light´J; stand-alone; Master/slave function; Light Captain
Beam angle:	120°
Beam angle (1/2 peak):	120°
Illuminance in Lux (lx):	Red (R) 1m: 438 lx, 3m: 61 lx, 6m: 18 lx Green (G) 1m: 633 lx, 3m: 88 lx, 6m: 25 lx Blue (B) 1m: 209 lx, 3m: 29 lx, 6m: 8 lx Cold white (CW) 1m: 2130 lx, 3m: 296 lx, 6m: 87 lx All 1m: 2696 lx, 3m: 380 lx, 6m: 112 lx
Lamp life:	50000 h
Luminous flux:	17103 lm
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	LCD display
Case handles:	1 pc/pcs
Dimensions:	Width: 64 cm Depth: 13 cm Height: 33,5 cm
Weight:	12,60 kg
Noise classification:	Class 0 (no noise at all)
Energy efficiency class (A - G):	F