

## EUROLITE LED PLL-576 CW/WW Panel

DMX-controlled surface light with 576 dual white LEDs, QuickDMX port, diffuser and barn doors

Art. No.: 40001899

GTIN: 4026397717273



**List price: 474.81 €**

incl. 19% VAT.

### Features:

- Additional frost filter provides a wide, soft and homogeneous light
- 4 barn doors to avoid blinding the audience and for protection during transport
- 288 powerful LEDs 0,5 W SMD 5730 cold white (CW)
- 288 powerful LEDs 0,5 W SMD 5730 warm white (WW)
- Dimmer electronic
- The device is cooled by temperature-controlled fan
- Control via DMX; master/slave function; stand-alone; quick select potentiometer for brightness and color temperature; CRMX by LumenRadio via USB (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional)
- Preprogrammed in Light Captain
- Flicker-free
- With a beam angle of 120°
- Variable color temperature 3000 K - 6000 K
- Direct color temperature selection for 69 preset values
- Very high color rendering index (CRI)
- With mounting bracket
- LCD display
- Rubber feet
- Mains input and output for power linking up to 8 units
- For application areas such as: Video and photography; stage; Trade fair and shop fitting; rental
- Very quiet working noise
- Application possibility: Suspended; standing; on stand

#### Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x frost filter, 4 x knurled screw

### Logistic

EAN / GTIN: 4026397717273

Weight: 6,55 kg

Length: 0.46 m

Width: 0.25 m

Height: 0.26 m

## Technical specifications:

|                              |                                                                                                                                                                                                                                         |
|------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply:                | 100-240 V AC, 50/60 Hz                                                                                                                                                                                                                  |
| Power consumption:           | 160 W                                                                                                                                                                                                                                   |
| IP classification:           | IP20                                                                                                                                                                                                                                    |
| Protection class:            | Protection class I                                                                                                                                                                                                                      |
| Power connection:            | Mains input via P-Con (blue), mounting version<br>power supply cord with safety plug                                                                                                                                                    |
| Power output:                | 1 x P-Con (gray), mounting version                                                                                                                                                                                                      |
| Fuse:                        | T 3,15 A fuse fix in power supply                                                                                                                                                                                                       |
| Lamp type:                   | LED lamp                                                                                                                                                                                                                                |
| LED type:                    | 288 x 0,5 W SMD 5730 cold white (CW)<br>288 x 0,5 W SMD 5730 warm white (WW)                                                                                                                                                            |
| DMX channels:                | 2-1; 2-2; 3-1; 3-2; 4                                                                                                                                                                                                                   |
| DMX input:                   | 3-pin XLR (M) mounting version<br>5-pin XLR (M) mounting version                                                                                                                                                                        |
| DMX output:                  | 3-pin XLR (F) mounting version<br>5-pin XLR (F) mounting version                                                                                                                                                                        |
| Cooling:                     | Temperature-controlled fan                                                                                                                                                                                                              |
| Control:                     | DMX; master/slave function; stand-alone; quick<br>select potentiometer for brightness and color<br>temperature; CRMX by LumenRadio via USB<br>(optional); QuickDMX via USB (optional); W-DMX<br>by wireless solution via USB (optional) |
| Preprogrammed in:            | Light Captain                                                                                                                                                                                                                           |
| Projection:                  | Flicker-free                                                                                                                                                                                                                            |
| Beam angle:                  | 120°                                                                                                                                                                                                                                    |
| Beam angle (1/2 peak):       | 120°                                                                                                                                                                                                                                    |
| Color temperature:           | 3000K - 6000K adjustable                                                                                                                                                                                                                |
| Color rendering index (CRI): | 93 Ra                                                                                                                                                                                                                                   |
| Illuminance in Lux (lx):     | Cold white (CW) 1m: 3752 lx, 3m: 453 lx, 6m: 134 lx<br>Warm white (WW) 1m: 3664 lx, 3m: 445 lx, 6m: 132 lx<br>All 1m: 5667 lx, 3m: 690 lx, 6m: 204 lx                                                                                   |
| Housing color:               | Black                                                                                                                                                                                                                                   |
| Attachment system:           | Mounting bracket                                                                                                                                                                                                                        |
| Display type:                | LCD display                                                                                                                                                                                                                             |
| Transport aid:               | Rubber feet                                                                                                                                                                                                                             |
| Dimensions:                  | Length: 44 cm<br>Width: 19,8 cm<br>Height: 22,3 cm                                                                                                                                                                                      |
| Weight:                      | 6,00 kg                                                                                                                                                                                                                                 |
| Noise classification:        | Class 1 (very slight noise, suitable for noise-<br>sensitive environments)                                                                                                                                                              |
| Legal specifications         |                                                                                                                                                                                                                                         |
| Special product:             | Not designed for household room illumination                                                                                                                                                                                            |

Intended use:

Show effect lighting