

EUROLITE LED PLL-576 CW/WW Panel

DMX-controlled surface light with 576 dual white LEDs, QuickDMX port, diffuser and barn doors

Art. No.: 40001899

GTIN: 4026397717273



Features:

- Additional frost filter provides a wide, soft and homogeneous light
- 4 barn doors to avoid blinding the audience and for protection during transport
- 288 LEDs 0.5 W SMD 5730 cold white (CW)
- 288 LEDs 0.5 W SMD 5730 warm white (WW)
- Dimmer electronic
- The device is cooled by temperature-controlled fan
- Control via DMX; master/slave function; stand-alone; quick select potentiometer for brightness and color temperature; CRMX by LumenRadio via USB (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional)
- Fixtures available for Light Captain
- Flicker-free
- With a beam angle of 120°
- Variable color temperature 3000 K - 6000 K
- Direct color temperature selection for 69 preset values
- Very high color rendering index (CRI)
- With mounting bracket
- LCD display
- Rubber feet
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; wedding/gala/events; Trade fair and shop fitting; theater; rental; video and photography
- Very quiet working noise
- Application possibility: Suspended; standing; on stand

Logistic

EAN / GTIN: 4026397717273

Weight: 6,55 kg

Length: 0.46 m

Width: 0.25 m

Height: 0.26 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	160 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Power output:	1 x P-Con (gray), mounting version
Fuse:	T 3.15 A fuse fix in power supply
Lamp type:	LED lamp
LED type:	288 x 0.5 W SMD 5730 cold white (CW) 288 x 0.5 W SMD 5730 warm white (WW)
DMX channels:	2-1; 2-2; 3-1; 3-2; 4
DMX input:	3-pin XLR (M) mounting version 5-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version 5-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	DMX; master/slave function; stand-alone; quick select potentiometer for brightness and color temperature; CRMX by LumenRadio via USB (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional)
Fixtures available for:	Light Captain
Projection:	Flicker-free
Beam angle:	120°
Beam angle (1/2 peak):	120°
Color temperature:	3000K - 6000K adjustable
Color rendering index (CRI):	93 Ra
Illuminance in Lux (lx):	Cold white (CW) 1m: 3752 lx, 3m: 453 lx, 6m: 134 lx Warm white (WW) 1m: 3664 lx, 3m: 445 lx, 6m: 132 lx All 1m: 5667 lx, 3m: 690 lx, 6m: 204 lx
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	LCD display
Transport aid:	Rubber feet
Dimensions:	Length: 44 cm Width: 19.8 cm Height: 22.3 cm
Weight:	6.00 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

- 1 x spotlight
- 1 x user manual
- 1 x power cord
- 1 x frost filter
- 4 x knurled screw