

EUROLITE LED PFE-200 3000K Profile Spot

PRO profile spotlight, 200 W warm white LED, zoom, shutter blades, CRI >95

Art. No.: 40001975

GTIN: 4026397705409



List price: 712.81 €

incl. 19% VAT.

Features:

- 1 powerful LED 200 W COB (chip-on-board) warm white (WW)
- Zoom manual; Focus manual
- With a beam angle of 14° - 41°
- Dimmer electronic; Dimmer speed (step response) adjustable
- Strobe effect
- The device is cooled by cooling fan
- Control via DMX; stand-alone
- Flicker-free
- Very high color rendering index (CRI)
- LCD display
- For application areas such as: Theater; Stage
- Preprogrammed in Light Captain
- Mains input and output for power linking up to 8 units
- Application possibility: Suspended; on stand

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x plug (male), 1 x filter frame

Logistic

EAN / GTIN: 4026397705409

Weight: 12,75 kg

Length: 0.74 m

Width: 0.36 m

Height: 0.35 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 135 W

IP classification: IP20

Protection class: Protection class I

Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Lamp type:	LED lamp
LED:	1 x 200 W COB (chip-on-board) warm white (WW)
Color temperature:	3157K
Equipment:	Zoom manual; Focus manual
DMX channels:	3
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	DMX; stand-alone
Preprogrammed in:	Light Captain
Projection:	Flicker-free
Beam angle:	14° - 41°
Beam angle (1/2 peak):	14 - 41°
Beam angle (1/10 peak):	14 - 41°
Color rendering index (CRI):	98 Ra
Lamp life:	15000 h
Luminous flux:	10188 lm
Housing color:	Black
Display type:	LCD display
Dimensions:	Length: 61,8 cm Width: 33,1 cm Height: 36,2 cm
Weight:	11,10 kg
Noise classification:	Class 3 (clearly perceptible sounds)
Energy efficiency class (A - G):	F