eurolite®

EUROLITE LED PFE-200 3000K Profile Spot

PRO profile spotlight, warm white 200 W LED, zoom, shutter blades, CRI >95

Art. No.: 40001975 GTIN: 4026397705409









List price: 712.81 €

incl. 19% VAT.

Features:

- 1 powerful LED 200 W COB (chip-on-board) warm white (WW)
- Zoom manual; focus manual
- With a beam angle of 14° 41°
- Dimmer electronic; Dimmer speed (step response) adjustable
- Strobe effect
- The device is cooled by cooling fan
- Control via DMX; stand-alone
- Flicker-free
- Very high color rendering index (CRI)
- LCD display
- For application areas such as: Theater; stage
- Preprogrammed in Light Captain
- Mains input and output for power linking up to 8 units
- Application possibility: Suspended; on stand Package contents
- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x plug (male), 1 x filter frame

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	135 W
IP classification:	IP20
Protection class:	Protection class I

Logistic

EAN / GTIN: 4026397705409 Weight: 12,75 kg Length: 0.74 m Width: 0.36 m Heigth: 0.35 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Lamp type:	LED lamp
LED type:	1 x 200 W COB (chip-on-board) warm white (WW)
Flash rate:	3,5 - 29 Hz
Equipment:	Zoom manual; focus manual
DMX channels:	3
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	DMX; stand-alone
Preprogrammed in:	Light Captain
Projection:	Flicker-free
PWM frequency:	2300 Hz
Beam angle:	14° - 41°
Beam angle (1/2 peak):	14 - 41°
Beam angle (1/10 peak):	14 - 41°
Color temperature:	3157K
Color rendering index (CRI):	98 Ra
Lamp life:	15000 h
Luminous flux:	10188 lm
Housing color:	Black
Display type:	LCD display
Dimensions:	Length: 61,8 cm Width: 33,1 cm Height: 36,2 cm
Weight:	11,10 kg
Noise classification:	Class 3 (clearly perceptible sounds)
Energy efficiency class (A - G):	F
EPREL-Nr:	1271171