

EUROLITE LED PFE-100 RGBW Profile Spot

PRO profile spotlight, 100 W 4in1 LED (RGBW), zoom, shutter blades

Art. No.: 40001982

GTIN: 4026397557015











List price: 784.21 €

incl. 19% VAT.

Features:

- 1 powerful LED 100 W COB (chip-on-board) 4in1 QCL RGBW
- Focus manual
- With a beam angle of 14° 41°
- Dimmer electronic; color blend stepless; color change adjustable; Dimmer speed (step response) adjustable
- Strobe effect
- The device is cooled by cooling fan
- Control via stand-alone; DMX; master/slave function
- With mounting bracket
- For application areas such as: Stage; installation; video and photography
- Preprogrammed in LED PC-Control 512; Light Captain
- OLED display
- Mains input and output for power linking up to 8 units
- Application possibility: Suspended; on stand

Package contents

- 1 x spotlight, 1 x power cord, 1 x filter frame, 1 x plug (male), 1 x user manual

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
IP classification:	IP20
Protection class:	Protection class I

Logistic

EAN / GTIN: 4026397557015

Weight: 12,85 kg Length: 0.74 m Width: 0.36 m Heigth: 0.34 m

Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (gray), mounting version
Lamp type:	LED lamp
LED type:	1 x 100 W COB (chip-on-board) 4in1 QCL RGBW
Flash rate:	0,5 - 10 Hz
Equipment:	Focus manual
DMX channels:	9
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; master/slave function
Preprogrammed in:	LED PC-Control 512; Light Captain
PWM frequency:	2300 Hz
Beam angle:	14° - 41°
Beam angle (1/2 peak):	14 - 41°
Beam angle (1/10 peak):	14 - 41°
Lamp life:	50000 h
Luminous flux:	11500 lm
Housing color:	Black matte
Attachment system:	Mounting bracket
Display type:	OLED display
Diameter mounting holes:	2 x Ø13mm
Material:	Aluminum casting; metal
Dimensions:	Length: 61,5 cm
	Width: 28 cm
Wolght	Height: 42 cm
Weight: Noise classification:	11,10 kg
-	Class 2 (slight noise)
Energy efficiency class (A - G):	
EPREL-Nr: Power cord	1243754
	2 4 5 2 1 105 \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \
Cable longth:	3 x 1,5 mm² H05VV-F
Cable length:	Approx. 1,2 m
Mounting bracket	4 v (642mm
Diameter mounting holes:	1 x Ø12mm
Material:	Aluminum casting, 7 mm
Filter frame	4 v (649 mm
Diameter mounting holes:	4 x Ø18mm
Material:	Aluminum, 1 mm
Color:	Black, matte
Plug (male)	Milester blue
Color:	White; blue