eurolite®

EUROLITE ML-56 MSD Multi Lens Spot sil

Spectrum of MSD lamps

Art. No.: 41600041 GTIN: 4026397425857



The article is no longer in our assortment.

Features:

- Spot with 4 exchangeable lenses (VNSP, NSP, MFL and WFL)
- High-quality die-cast housing for highest stability
- High-quality aluminum reflector
- With color-filter frame
- Optional barndoors
- For extremely powerful MSD lamp
- Ideal for theatres, large stages and mobile use

Logistic

EAN / GTIN: 4026397425857 Weight: 7,50 kg Length: 0.28 m Width: 0.28 m Heigth: 0.52 m

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	345 W
IP classification:	IP20
Lamp type:	Discharge lamp
Beam angle (1/2 peak):	VNSP 15° x 34°
	NSP 19° x 34°
	MFL 21° x 34°
	WFL 30° x 51°
Housing color:	Silver
Dimensions:	Width: 27,5 cm
	Depth: 27,5 cm

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

	Height: 39 cm
Weight:	6,85 kg
Beam angle VNSP/NSP/MFL/WFL:	15/20/21x36/30x53°
Dimensions:	275 x 275 x 390 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting