# eurolite

# EUROLITE LED KKL-12 Floodlight 3200K white

Warm white 12 W LED light on an extension arm with clamp holder

机杨菊

# The article is no longer in our assortment.

## **Description:**

The Eurolite KKL-12 LED floodlight illuminates trade fair booths, shop windows, workshops and even weatherproof outdoor areas.

You can purchase the KKL-12 in three simple casing colors: black, white and silver.

### Features:

- Inclination-angle of the device head: horizontally approx. 320°, vertically approx. 85°
- Unique design
- 12 powerful LEDs 1 W high-power warm white (WW)
- The device is cooled by passive convection cooling
- Control via plug and play
- Easy installation
- With a beam angle of 40°
- Various versions available
- Silent operation
- For application areas such as: Advertisement/Shop window; Trade fair and shop fitting **Package contents**
- 1 x spotlight, 1 x knurled screw, 1 x plate, 1 x user manual

#### **Technical specifications:** 100-240 V AC, 50/60 Hz Power supply: Power consumption: 12 W

Logistic

EAN / GTIN: 4026397606676 Weight: 0,95 kg Length: 0.46 m Width: 0.14 m Heigth: 0.10 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.



Art. No.: 41600463 GTIN: 4026397606676





IP classification:	IP20
Power connection:	Fixed power supply cord with safety plug
Cable length:	Approx. 1,5 m
Lamp type:	LED lamp
LED type:	12 x 1 W high-power warm white (WW)
Cooling:	Passive convection cooling
Control:	Plug and play
Setup:	Easy installation
Beam angle:	40°
Beam angle (1/2 peak):	40°
Beam angle (1/10 peak):	75
Color temperature:	3200K
Illuminance in Lux (Ix):	3m: 130 lx, 6m: 39 lx
Luminous flux:	752 lm
Housing color:	White
Dimensions:	Length: 45 cm
	Width: 13 cm
	Depth: 12 cm
Weight:	0,79 kg
Noise classification:	Class 0 (no noise at all)
Energy efficiency class (A - G):	G
EPREL-Nr:	2011802