

EUROLITE LED KKL-30 Floodlight 4100K silver

30 W LED floodlight with extension arm and screw terminal for fixation

Art. No.: 41600467

GTIN: 4026397646894



List price: 71.28 €

incl. 19% VAT.

Features:

- Head tiltable 90°
- Unique design
- Easy mounting via screw clamp
- For tabletops with up to 40 mm strength
- 1 powerful LED 30 W COB (chip-on-board) neutral white (NW)
- The device is cooled by passive convection cooling
- Control via plug and play
- With a beam angle of 59°
- Good color rendering index (CRI)
- Various versions available
- Silent operation
- For application areas such as: Advertisement/Shop window; Trade fair and shop fitting
- Application possibility: Suspended; wall mounting

Package contents

- 1 x spotlight, 1 x knurled screw, 1 x plate, 1 x user manual

Logistic

EAN / GTIN: 4026397646894

Weight: 0,97 kg

Length: 0.61 m

Width: 0.14 m

Height: 0.05 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	31 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug

Cable construction:	3 x 0,75 mm² H05VV-F
Cable length:	Approx. 1,2 m
Lamp type:	LED lamp
LED type:	1 x 30 W COB (chip-on-board) neutral white (NW)
Cooling:	Passive convection cooling
Control:	Plug and play
Beam angle:	59°
Beam angle (1/2 peak):	59°
Beam angle (1/10 peak):	106°
Color temperature:	4100K
Color rendering index (CRI):	83 Ra
Illuminance in Lux (lx):	1m: 1275 lx, 3m: 176 lx, 6m: 46 lx
Luminous flux:	1769 lm
Housing color:	Silver
Dimensions:	Length: 62 cm Width: 13,5 cm Depth: 8,5 cm
Weight:	0,83 kg
Noise classification:	Class 0 (no noise at all)
Energy efficiency class (A - G):	G
EPREL-Nr:	1273258
Knurled screw	
Thread:	X 60 mm
Plate	
Material:	Metal, 1,5 mm
Color:	Silver, matte
Dimensions:	Diameter: Ø 2 cm